

Our WellBAC® Comfort and Comfort Plus carpet comes with open-cell, cushion backing as a standard. It is designed to allow floors to breathe and moisture to evaporate when used in combination with our Non-Reactive

With Milliken carpet, moisture vapour can travel freely through our open-cell cushion backing, venting naturally from the seams.

Hardback carpet often traps moisture vapour, causing water condensation to form underneath the tiles.

Standard (NRS) adhesive.

Milliken

Renovation without aggravation

When your subfloor is substandard, our flooring's got you covered.

Install Milliken carpet tile without costly moisture mitigation.

No need to apply floor surface primer.

Carpet tile can be installed over old adhesives.

WellBAC® open-cell carpet backing allows floors to breathe and moisture to evaporate.

RENOVATION	CARPET	
INSTALLATION	MILLIKEN CUSHION BACK CARPETS WITH NON-REACTIVE ADHESIVE	TYPICAL HARDBACK CARPET WITH MOISTURE MITIGATION
Required removal of existing adhesive	NO	YES
Required Use of Moisture Suppressant or Concrete Sealer	NO	YES
Create new concrete surface (Mechnical Abrasion)	NO	OFTEN
TESTING		
Bond Test	YES	YES
RH and pH Test	NO *	YES
Bond Warranty	LIFETIME	TYPICALLY ≤ 10 YEARS

^{*} With confirmed vapour barrier under the ground-floor slab.

