



2.5mm Fortified Foundations Milliken

Final Assembly: Zhenjiang, Jiangsu, China

Life Expectancy: 25 Year(s)

End of Life Options: Recyclable (100%)

Ingredients:

Calcium carbonate; Polyvinyl chloride; Octadecanoic Acid, 10-Chloro-9-Methoxy, Methyl Ester; Dioctyl terphthalate, DOTP; Soybean oil, epoxidized; Calcium Stearate; Zinc Stearate; Carbon black; Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-aminoethanol and 2-(chloromethyl)oxirane; Hexamethylene Diacrylate; 2-Propenoic acid, (1-methyl-1,2-ethanediyl) bis[oxy(methyl-2,1-ethanediyl)] ester; Dipropylene Glycol Diacrylate; Trimethylolpropane Triacrylate; 2-hydroxyethyl Methacrylate; Propoxylated neopentyl glycol Diacrylate; 2-hydroxy-2-methyl-phenyl-propan-1-one; 2,4,6-trimethyl benzoyl diphenyl phosphine oxide

Living Building Challenge Criteria:

I-13 Red List:

- | | |
|--|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input checked="" type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.1-2010

I-14 Responsible Sourcing: Not Applicable

MKN-0010

EXP. 01 MAR 2026

Original Issue Date: 2015