

## 2.5mm Fortified Foundations and **Original Collection** Milliken

Final Assembly: Zhenjiang, Jiangsu, China

**Life Expectancy:** 25 Year(s)

End of Life Options: Recyclable (100%)

## **Ingredients:**

Calcium carbonate; Polyvinyl chloride; Octadecaneoic Acid, 10-Chloro-9-Methoxy, Methyl Ester; Dioctyl terphthalate, DOTP; Soybean oil, epoxidized; Calcium Stearate; Zinc Stearate; Carbon black; Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-aminoethanol and 2-(chloromethyl)oxirane; Hexamethylene Diacrylate; 2-Propenoic acid, (1-methyl-1,2ethanediyl) bis[oxy(methyl-2,1-ethanediyl)] ester; Dipropylene Glycol Diacrylate; Trimethylolpropane Triacrylate; 2hydroxyethyl Methacrylate; Propoxylated neopentyl glycol Diacrylate; 2-hydroxy-2-methyl-phenyl-propan-1-one; 2,4,6trimethyl benzoyl diphenyl phosphine oxide

## **Living Building Challenge Criteria:**

## I-13 Red List:

☐ LBC Red List Free

☐ LBC Red List Approved

**VOC Content: Not Applicable** 

% Disclosed: 100% at 100ppm

■ Declared

**I-10 Interior Performance:** CDPH Standard Method v1.1-2010

I-14 Responsible Sourcing: Not Applicable

MKN-0010 EXP. 01 APR 2025 Original Issue Date: 2015