

Declare.

5mm Rigidform LPT Milliken

Final Assembly: Hanyu City, Saitama, Japan

Life Expectancy: 15 Year(s)

End of Life Options: Recyclable (100%)

Ingredients:

Calcium carbonate; Magnesium hydroxide; Polypropylene; 1-Propene, polymer with ethene; 1-Octene, polymer with ethene; Polyethylene; Poly(oxy-1,2-ethanediyl), α -tridecyl- ω -hydroxy-, phosphate; Zinc Stearate; Polyurethane; calcium carbonate; Poly(oxy-1,2-ethanediyl), α -tridecyl- ω -hydroxy-; Diazene-1,2-dicarboxamide (C,C'-azodi(formamide)); 2-Propenoic acid, 1,1'-[2-[[[3-[(1-oxo-2-propen-1-yl)oxy]-2,2-bis[[[(1-oxo-2-propen-1-yl)oxy]methyl]propoxy]methyl]-2-[[[(1-oxo-2-propen-1-yl)oxy]methyl]-1,3-propanediyl] ester]; Hexamethylene Diacrylate; Ammonium polyphosphate; Aluminum Oxide; Dipropylene Glycol Diacrylate; 1,3,5-Triazine-2,4,6(1H,3H,5H)-trione, 1,3,5-tris(2-hydroxyethyl)-; 2-Propenoic acid, monoester with 1,2-propanediol; Amorphous silica; methyl benzoylformate; Fatty acids, C18-unsatd., dimers, di-Me esters, hydrogenated polymers with adipic acid, 5-amino-1,3,3-trimethylcyclohexanemethanamine, 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane and 3-methyl-1,5-pentanediol; Carbon black; Zinc oxide

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|-------------------------------------------------------|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

MKN-0043

EXP. 01 SEP 2025

Original Issue Date: 2022