

RENASCI (RESILIENT FLOORING)

Milliken N/XT LIFE™ Flooring System (PVC-FREE)

Construction	Mixed Polymers
Finish	Integrated Polyurethane
Wear Layer Thickness	0.50mm
Tile Size:	50cm x 100cm
Overall Thickness (Nominal)	6.5mm (±0.3mm)
Recyclable	100%
Pieces Per Box	6 pieces
Weight Per Box	26.5kg
Quantity Per Box	3.00m ²

Critical Radiant Flux (AS ISO 9239-1)	2.9 kW/m ²
Smoke Rate (AS ISO 9239-1)	597%.min
Slip Resistance Classification	P3 & R10
Scratch Resistance (0.6Kg mass) (ISO 1518.1 - Part A)	No Scratch
Determination of Dimensional Stability & Curling after Exposure to Heat (ISO 23999)	≤0.25%; Curl ≤2mm
Castor Chair Resistance (ISO 4918, 5000 cycles)	PASS
Total VOC Emissions (ISO 10580)	≤ 0.30 (mg/m ² /h)

Recommended Installation Methods	Glue Down Only Half-Drop Ashlar Random Ashlar Herringbone
Recommended Area of Use	Commercial Residential
Warranties	10-year Limited Commercial Wear Warranty

RENASCI™

Made from 80% carpet waste and 20% soft plastic waste, Renasci* doesn't just reduce landfill, it redefines possibility. With low embodied carbon, high performance, and full recyclability, it's not just flooring. It's **DAY ONE** of a closed-loop future. A lighter footprint. A cleaner path forward. And a powerful reminder that from waste, something remarkable can be born again.

Renasci* - patent pending

N/XT LIFE™ CIRCULARITY PROGRAM

N/XT Life™ Circularity Program emphasizes material circularity and environmental responsibility in flooring design. By focusing on reducing, reusing, and recycling through strategic partnerships, the **N/XT Life™ Circularity Program** gives flooring a second life. With the use of Red List Free materials, prioritization of recycled yarn, and the innovative ways Milliken looks to extend carpet life - we hope to create a positive impact on the world around us.