

### CIRCULAR RELATIONSHIPS (WELLBAC® COMFORT - ORG18)

Dunes | Wave Break | Rock Grain | Tussock | Loop Track | Fossil Point

Modular Tiles and Planks

PRODUCT SPECIFICATION				
Standard Backing	Cushion Backing   WellBAC® Comfort (PVC FREE) (Non-Reactive Cushion Backing)			
Acoustic Value	Noise Reduction Coefficient - NRC ≥ 0.25			
	Impact Sound Pressure Level - Ln,w ≤ 47dB			
Concrete Slab Moisture Mitigation	Site-Related Solutions (SRS): Milliken cushion-backed tile + Non-Reactive Standard Adhesive means installation 45 days after a new concrete pour, fully warranted no moisture testing required. Refer to <a href="https://www.millikenfloors.com.au">www.millikenfloors.com.au</a>			
Antiviral   Antibacterial	MGUARD+ Antiviral and Antibacterial Treatment. For further information refer to <a href="https://www.millikenfloors.com.au">www.millikenfloors.com.au</a>			

#### **WELLBAC®**

Milliken WellBAC® open cell foam cushion provides superior durability, appearance retention and cushioning.



# UNDERFOOT COMFORT Up to 24% greater underfoot comfort for enhanced ergonomics whilst standing.



ACOUSTIC VALUES
Up to 50% improved acoustics for quieter, more productive spaces.



INDOOR AIR QUALITY
Enhanced Indoor Air Quality
(Green Label Plus™
Certified Low VOC) for
improved occupant and

installer well-being.



MOISTURE MITIGATION Industry leading moisture management with non-reactive backings to enhance the installation process, saving time and money.



MATERIAL HEALTH

3rd party Verified

Declare™ Red-List Free
products for occupant and
installer well-being.

Flammability CHF/CRF = 7.5kW/m<sup>2</sup>



CIRCULARITY
100% Recyclable through the
Milliken N/XT LIFE circularity
program for both installation
waste and end-of-life.

Construction	Tufted, Texture Loop		
Tile Ci-e	50cm x 50cm, 25cm x		
Tile Size	100cm, 100cm x 100cm		
Vous Time	Milliken Certified		
Yarn Type	100% Nylon		
Stain Resist   Soil Release	StainSmart®		
·			
Dye Method	PrintWorks™		
Gauge	1/12		
Stitches Per Inch	11		
Tufts	132/in <sup>2</sup> (2,044/100cm <sup>2</sup> )		
Total Pile Mass	18oz/yd² (610g/m²)		
Recyclable	100%		
Recycled Content by Total Weight	44%		
Nominal Total Thickness	8.5mm		
Nominal Pile Thickness	3.0mm		
Nominal Total Weight	96 oz/yd² (3,251g/m²)		

(Radiant Panel Test)	Smoke Value = 173%. min	
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours	
Static Electricity (AATCC-134) 20% R.H., 70° F	≤3.5V	
Indoor Air Quality CRI Green Label Plus™	≤ 0.5mg/m³ (GLP0793)	
VOC	Pass (ISO 10580:2010)	
ACCS Grading	CEHD 4*, REHD2 6*, Suitable for Stairs	
Environmental	ECS Grading - Level 4 + (Core +	
	No Chemicals of Concern + EPD +	
	Carbon Neutral)	
	Declare - RED LIST FREE	
	Cradle to Cradle - Silver	
	M/PACT™ Carbon Neutral Program	
	Environmental Product Declaration (EPD)	
	Health Product Declaration (HPD)	
	Works With WELL	

The recognised Product Certification Initiatives in the Green Star rating tools that contribute to the responsible product value of Milliken carpet tiles are as listed. The Green Building Council of Australia recognises Responsible Products that may contribute to a Green Star rating through its Responsible Credits (rpv).

- 1. ECS Carpet Standard v2.2
- 2. Cradle to Cradle
- 3. Declare 2.0 Red List Free
- 4. Science-Based Targets Initiative (SBTi)

GBCA
Responsible Product Value
30 rpv

	Recommended	Rock Grain (50cm x 50cm): N	Nonolithic   Brick (Horizontal)	Dunes (1m x 1m): Monolithic	
	Installation Methods	Fossil Point, Loop Track, Tussock (50cm x 50cm): Monolithic   Wave Break (25cm x 1m): All Plank Methods			m): All Plank Methods
	Recommended Area of Use	Commercial Extra Heavy Duty			
Ī	Warranties	20-year	20-year	20-year Dimensional	20-year Castor Chair
		Wear Warranty	Anti-Static Warranty	Stability Warranty	Wear Warranty



















## Milliken

### **WORKS WITH WELL**

Milliken's commitment to advancing products and solutions that support human health and well-being is long-standing.



As a founding member of the **Well Living Lab** and a **Well Portfolio Member**, we aspire to design products that enhance the well-being and quality of life of indoor spaces.

We are proud to have been granted the **Works with WELL™** licence across an extensive selection of our global product portfolio, demonstrating how Milliken floor covering products align with specific strategies in the WELL Standard, the leading global standard for health and well-being.

The Works with WELL trademark licensing program recognises products and solutions that contribute to achieving specific features in the WELL Standard. Products that have earned the Works with WELL mark have been validated through one or more review cycles to give specifiers the maximum confidence in their material selections, whether working on a WELL-certified project or simply wanting to ensure they are adopting best practices for healthy, sustainable, people-first spaces for their clients.



CONCEPT		FEATURE	FEATURE NAME	
WATER		W07.2	Design Interiors for Moisture Management	
13	MOVEMENT	V02.4	Provide Support at Standing Workstations	
	MATERIALS	X05.2	Select Compliant Architectural and Interiors Products	
		X06.2	Restrict VOC Emissions from Furniture, Architectural and Interior Products	
		X07.1	Select Products and Disclosed Ingredients	
		X07.2	Select Products with Enhanced Ingredients Disclosure	
		X07.3	Select Products with Third-Party Verified Ingredients	
		X08.1	Select Materials with Enhanced Chemical Restrictions	
		X08.2	Select Optimised Products	

Driven by the global demand for healthier places and healthier organisations that support people to thrive, WELL adoption has grown exponentially since its launch in 2014. WELL strategies have been used in over 5 billion square feet of space, supporting the health and well-being of an estimated 17 million people in more than 74,000 locations spanning over 130 countries.

Contact one of our team of WELL Accredited Professionals for support with your next WELL Certified project at millikenanzenguiries@milliken.com.

















