

Declare. SM

2mm & 2.5mm Local Measure Milliken

Final Assembly: Fostoria, Ohio, US

Life Expectancy: 25 Year(s)

End of Life Options: Recyclable (100%)

Ingredients:

Calcium magnesium carbonate; **Polyvinyl chloride**; Dioctyl terphthalate, DOTP; Calcium Stearate; Zinc Stearate; Carbon black; Hexanedioic acid, polymer with 1,2-ethanediol and 1,6-diisocyanato-2,2,4(or 2,4,4)-trimethylhexane, 2-hydroxyethyl acrylate-blocked; Dipropylene Glycol Diacrylate; Poly(oxy-1,2-ethanediyl), α -(1-oxo-2-propenyl) ω -[(1-oxo-2-propenyl)oxy]-; Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[N-(4-chloro-2,5-dimethoxyphenyl)-3-oxo-; Calcium Chloride; Trimethylolpropane Triacrylate; Ethyl Acetate

Living Building Challenge Criteria:

I-13 Red List:

- | | |
|--|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input checked="" type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

MKN-0034

EXP. 01 JUN 2024

Original Issue Date: 2020