

SPECIFICATION SHEET DATE: 16/8/2023

# METRO PARK (RIGIDFORM™ SPC)

Stone

Milliken Hybrid Flooring System

## M/PACT™

CARBON NEUTRAL PROGRAM

When you choose M/PACT™ products, you can be sure your choice is carbon neutral. M/PACT™ carbon neutral products offset the raw materials and manufacturing carbon footprint\* by using 3rd party Verified Carbon Standard Credits that support renewable energy and carbon reduction technologies to help fight climate change.

\*as calculated and verified through a ISO14025/ISO14040 compliant LCA and published in third party EPD.

<b>Standard Backing</b>	Integrated Cushion Backing: Pre-attached underlayment minimises sound, is shock absorbent, provides comfort underfoot and further assists with the concealment of subfloor imperfections.
<b>Acoustic Value</b>	Impact Sound Pressure Level - Ln,w = 58dB

<b>Construction</b>	High performance Rigid Core Flooring
<b>Finish</b>	ProGuard™ Reinforced Polyurethane Coating
<b>Wear Layer Thickness</b>	0.55mm
<b>Tile Size</b>	18" x 36" (45.7cm x 91.4cm)
<b>Overall Thickness</b>	6.2mm
<b>Edge Profile</b>	Micro Bevel
<b>Recyclable</b>	100%
<b>Pieces Per Box</b>	5 pc
<b>Weight Per Box</b>	20.1kg
<b>Quantity Per Box</b>	2.17m <sup>2</sup>
<b>Environmental</b>	Declare Carbon Neutral GreenRate by Global Green Tag Best Practice PVC Environmental Product Declaration (EPD)

<b>Use Classification (ISO 10582)</b>	Class 33 Heavy Duty Commercial
<b>Critical Radiant Flux</b>	9.6kW/m <sup>2</sup>
<b>Smoke Density</b>	154%.min
<b>Slip Resistance Classification</b>	P3 & R10
<b>Heat Stability of Colour Change (ASTM F1514)</b>	PASS
<b>Light Stability (ASTM F1515)</b>	PASS
<b>Static Coefficient of Friction (ASTM D2047)</b>	PASS
<b>Determination of Dimensional Stability &amp; Curling after Exposure to Heat (ISO 23999)</b>	PASS
<b>Resistance to Chemicals (ASTM F925)</b>	PASS
<b>Static Load Limit (ASTM F970)</b>	PASS

<b>Recommended Installation Method(s)</b>	SecureLock™ locking mechanism
<b>Recommended Area of Use</b>	Commercial   Residential
<b>Warranties</b>	15-year Wear Warranty



Alliance Founding Member



Milliken Hybrid Flooring System is highly durable resilient flooring engineered with the highest quality raw materials to provide unsurpassed performance and enduring aesthetics.

Milliken Hybrid Flooring System is 100% ortho-phthalate-free.

Milliken Hybrid Flooring System is manufactured at facilities that are ISO 9001 and ISO 14001 compliant.