Clerkenwell - EC1 - Tile

M50 CARPET TILING

130 Carpet Body Tiles

Location: Refer to Finishes Schedule

Preparation: According to the guidelines laid out in the Contract

Flooring Association's "Guide to Contract Flooring".

Carpet Tiles: Manufacturer and reference Milliken "Clerkenwell - EC1 -

Tile"

Size: 500 x 500mm nominal to be die cut for consistent

tolerance.

Colour: Refer to Finishes schedule
Pattern: Refer to Finishes schedule
Construction: Tufted Textured Tip-Shear
Fibre: Solution Dyed Nylon 6 6

Chosen for soil hiding and resilience.

Backing: High-density, open-cell polyurethane foam. 90% recycled

Improved comfort, acoustics and wear performance.

Yarn: Spun yarn, heat set.

Pattern: EC1

Finished Dimensions: Module = 500×500 mm

Pile Weight = 675 g/m² Pile Height = 3.3mm

Tuft Density = 198,060 per m² Total Thickness = 10.4 mm Total Weight = 4350 g/m²

Warranties: 15 year wear warranty

Lifetime Antistatic Latent Defects

Zatom Borotto

Method of Laying: By Milliken Approved Contractor.

In strict accordance with Milliken installation

recommendations.

Special Requirements: Maintenance method must be demonstrated to ensure

not only appearance retention but also to leave carpet in

Milliken.

hygienic condition.