

# EXCEED (BK16 BASE)

Action | Energy | Buzz | Speed

Modular Tiles

## M/PACT™

CARBON NEUTRAL PROGRAM

When you choose M/PACT™ products, you can be sure your choice is carbon neutral. M/PACT™ carbon neutral products offset the raw materials and manufacturing carbon footprint\* by using 3rd party Verified Carbon Standard Credits that support renewable energy and carbon reduction technologies to help fight climate change.

\*as calculated and verified through a ISO14025/ISO14040 compliant LCA and published in third party EPD.

|   |   |  |   |  |  |
|---|---|--|---|--|--|
| <p><b>WELLBAC®</b></p> <p>Milliken WellBAC® open cell foam cushion provides superior durability, appearance retention and cushioning.</p> | <p>Up to 24% greater underfoot comfort for enhanced ergonomics whilst standing.</p> | <p>Up to 50% improved acoustics for quieter, more productive spaces.</p> | <p>Industry leading moisture management with non-reactive backings to enhance the installation process.</p> | <p>3<sup>rd</sup> party Verified Red-List Free products for occupant and installer well-being.</p> | <p>Enhanced Indoor Air Quality (Low VOC) for improved occupant and installer well-being.</p> |
|---|---|--|---|--|--|

|  |   |
|--|---|
| <b>Standard Backing</b>                  | Cushion Backing<br>WellBAC® Comfort (PVC FREE) (Non-Reactive Cushion Backing)   |
| <b>Acoustic Value</b>                    | Noise Reduction Coefficient - NRC ≥ 0.25<br>Impact Sound Pressure Level - Ln,w ≤47dB  |
| <b>Concrete Slab Moisture Mitigation</b> | Site-Related Solutions (SRS). Milliken Cushion backed tile + Non-Reactive Standard adhesive means installation 60 days after a new concrete pour, fully warranted no moisture testing required. Refer millikenfloors.com.au |
| <b>Antiviral   Antibacterial</b>         | MGUARD+ Antiviral and Antibacterial Treatment. Further information refer to millikenfloors.com.au   |

|                                    |   |
|------------------------------------|---|
| <b>Construction</b>                | Tufted, Textured Loop                           |
| <b>Tile Size</b>                   | 50cm x 50cm                                     |
| <b>Yarn Type</b>                   | Milliken Certified 100% Nylon                   |
| <b>Stain Resist   Soil Release</b> | StainSmart®                                     |
| <b>Dye Method</b>                  | PrintWorks™                                     |
| <b>Gauge</b>                       | 1/12  |
| <b>Stitches Per Inch</b>           | 11.6  |
| <b>Tufts</b>                       | 139/in <sup>2</sup> (2,126/100cm <sup>2</sup> ) |
| <b>Total Tile Mass</b>             | 16 oz/yd <sup>2</sup> (543g/m <sup>2</sup> )    |
| <b>Recyclable</b>                  | 100%  |
| <b>Nominal Total Thickness</b>     | 8.2mm   |
| <b>Nominal Pile Thickness</b>      | 2.1mm   |
| <b>Nominal Total Weight</b>        | 94 oz/yd <sup>2</sup> (3,184 g/m <sup>2</sup> ) |

|   |   |
|---|---|
| <b>Flammability (Radiant Panel Test)</b>              | CHF/CRF = 5.1kW/m <sup>2</sup> ,<br>Smoke value = 240%.min  |
| <b>Lightfastness (AATCC 16E)</b>                      | ≥ 4.0 at 80 Hours   |
| <b>Static Electricity (AATCC-134) 20% R.H., 70 °F</b> | ≤ 3.5KV   |
| <b>Indoor Air Quality CRI Green Label Plus™</b>       | <0.5mg/m <sup>3</sup> (GLP3237)   |
| <b>VOC</b>  | Pass (ISO 10580:2010)   |
| <b>ACCS Grading</b>                                   | CEHD 4*, REHD2 6*<br>Suitable for stairs  |
| <b>Environmental</b>                                  | ECS Grading -<br>Level 4 (Certificate No. 20078)<br>Declare -<br>3 <sup>rd</sup> Party Verified RED LIST FREE<br>Cradle to Cradle - Silver<br>Carbon Neutral<br>Environmental Product Declaration (EPD)<br>Health Product Declaration (HPD) |

|   |  |                                    |
|---|--|------------------------------------|
| <b>Recommended Installation Method(s)</b> | Speed, Buzz, Action: Monolithic   Quarter Turn<br>Energy: Brick (Horizontal) |                                    |
| <b>Recommended Area of Use</b>            | Commercial Extra Heavy Duty  |                                    |
| <b>Warranties</b>                         | 15-year Wear Warranty  | 15-year Anti-Static Warranty       |
|   | 15-year Dimensional Stability Warranty                                       | 15-year Castor Chair Wear Warranty |



Alliance  
Founding  
Member



This WellBAC® cushion backing carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.