

Adhesives

LVT

ADHESIVE TYPE	RH LEVEL	ADHESIVE	LVT TYPE
TROWEL 	up to 95%	LVT Standard <ul style="list-style-type: none"> For on-grade installations vapor retarder required Approved for all grade renovations where concrete pH levels are between 5-12 and RH is less than 95% INSTALL 45 days after new pour with RH testing	2 mm, 2.5 mm & 5 mm FlexForm™ LVT
	over 95%	LVT Moisture XT <ul style="list-style-type: none"> Unlimited Moisture Protection NO moisture or PH testing required NO moisture vapor barrier required NO RH, PH, or MVER limits INSTALL 45 days after new pour / NO moisture testing required	2 mm, 2.5 mm, 5 mm FlexForm™ LVT 4.5 mm RigidForm Free™
SPRAY 	up to 98%	Mosaic 98 - Spray <ul style="list-style-type: none"> Approved for all grade renovations where concrete pH levels are between 5-11 and RH is equal to or less than 98%. INSTALL 45 days after new pour with RH testing	2 mm, 2.5 mm, 5 mm FlexForm™ LVT 5 mm FlexForm Sound™ LVT* <small>*Hospitality Rooms only, no public areas</small>
	over 95%	Mosaic Moisture XT-Spray <ul style="list-style-type: none"> For use where very high moisture is a concern. NO moisture testing is required. NO RH or pH limits. INSTALL 45 days after new pour / NO testing required	5 mm FlexForm™ LVT
TROWEL 	up to 95%	Mosaic 95 <ul style="list-style-type: none"> Approved for all grade renovations where concrete pH levels are between 5-11 and RH is equal to or less than 95% INSTALL 45 days after new pour with RH testing	5 mm FlexForm™ LVT 5 mm FlexForm Sound™ LVT 4.5 mm RigidForm Free™