SPECIFICATION SHEET Date: 26.02.2024 Revision 1

PAINTED GARDEN



Construction	Tufted, Luxury Textured Loop Pile		
Face Fibre	ECONYL® 100% recycled Nylon		
Soil Release	StainSmart® for stain resist and soil release		
Finished Face Weight	1010 g/m ²		
Gauge	47.2 / 10 cm		
Rows	44.0 / 10 cm		
Tuft Density	207,874 /m ²		
	5.3 mm		
Finished Pile Height	5.3 mm		
Finished Pile Height Standard Backing	5.3 mm WellBAC® Comfort Plus 90% Recycled Polyurethane cushion. Available with TractionBack® on request		
	WellBAC® Comfort Plus 90% Recycled Polyurethane cushion.		
Standard Backing	WellBAC® Comfort Plus 90% Recycled Polyurethane cushion. Available with TractionBack® on request		
Standard Backing Nominal Total Thickness	WellBAC® Comfort Plus 90% Recycled Polyurethane cushion. Available with TractionBack® on request 12.1 mm		
Standard Backing Nominal Total Thickness Plank Size	WellBAC® Comfort Plus 90% Recycled Polyurethane cushion. Available with TractionBack® on request 12.1 mm 25 cm x 100 cm		

PEK	FOR	MA	NCE

Flammability (Euroclassification EN13501:1-2018) Class Cfl - s1 Flammability (Radiant Panel ASTM-E-648) Class 1 Flammability (Hot Metal Nut BS4790) Low Radius of Char Use Classification (EN 1307) Class 33 Heavy Commercial Use Castor Chair (BS EN 985:2001) Class A - Intensive use (r value \geq 2.4) Static Electricity (ISO 6356) Pass ≤ 2.0 KV Permanent Conductive Fibre Impact Sound (ISO 10140-3) $37 \text{ dB } \Delta L_w$ Sound Absorption (ISO354) 0.35 Class D 125Hz 0.00, 250Hz 0.15, 500Hz 0.40, 1000Hz 0.25, 2000Hz 0.40, 4000Hz 0.50 Alpha p values

ENVIRONMENTAL

70% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors, 5.71 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A3) Cradle to Gate footprint 100% off set

WARRANTIES

15 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

































































INSTALLATION





Ashlar Half Drop



CE / UKCA











