Mosaic 95



ADHESIVE

For Mixed Media

Carpet Tile 5 mm FlexForm™ LVT 5 mm FlexForm™ Sound LVT





















UP TO 11

UP TO 95%

30+ min

WORKING TIME

ROLL FLOOR within 1 hr (LVT Only)

CURE TIME

LIGHT TRAFFIC HEAVY TRAFFIC 12 hrs 24 hrs

HEAVY ROLLING LOADS: 72 hrs



Aggressive-Tack Mixed-Media Adhesive

For use with RH up to 95%

Installation after new pour: 45 days



The Benefits of Milliken Adhesives Milliken offers adhesive solutions for any scenario:

- Modular carpet, LVT, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required

1/16" x 1/16" x 1/32"

U-Notch

FLOORING TYPE

Carpet Tile 5 mm FlexForm LVT 5mm FlexForm Sound LVT* *Semi-Wet or Wet application required

ESTIMATED COVERAGE 185-245 sf/gal



3/8" Short Nap Paint Roller **FLOORING TYPE**

Carpet Tile

ESTIMATED COVERAGE 200 - 260 sf/gal

Mosaic 95



PRODUCT CHARACTERISTICS	Product Classification	Trowel pressure sensitive adhesive
	Base Chemistry	Acrylic polymer
	Solids Content	40% to 60%
	Density	8.3 lbs. per U.S. gal. (1.0 g per mL)
	Appearance	Light tan
	Application	Trowel (Carpet Tile & LVT) or roller (carpet tile only)
	Flash Point	> 212°F (100°C)
	Shelf Life	2 years (unopened)
MOISTURE	RH	95%
	рН	Up to 11
TIME	Flash Time (permanent bond - LVT only)	0 min
	Flash Time (pressure-sensitive - carpet tile)	30 min or until dry
	Working Time	15 mins (permanent bond- LVT only), 8 hrs (PSA)
	Roll & Cross Roll Floor (75- 100lb roller)	Within 1 hour after installation (LVT only)
TRAFFIC	Light Traffic	12 hrs
	Heavy Traffic	24 hrs
	Heavy Rolling Loads	72 hrs
SUSTAINABILITY	Total VOCs	0.5 mg/m³ or less
	Compliant with	California DPH Section 01350 Version 1.2
	Certifications	CRI Green Label Plus

STORAGE This product should be stored at temperatures between 50-90°F (10-32° C). While this product is freeze-thaw

stable, it is necessary to protect it from freezing.

CAUTION DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately.

KEEP OUT OF REACH OF CHILDREN.

WARRANTY For Milliken installation instructions and warranties, visit millikenfloors.com.

