

## OBEX™ Tile Cut - Galaxy, Cross, Thread M50 ENTRANCE FLOORING

<b>130</b>	Entrance Flooring Tiles
<b>Location:</b>	Refer to Finishes Schedule
<b>Preparation:</b>	According to the guidelines laid out in the Contract Flooring Association's "Guide to Contract Flooring".
<b>Tiles:</b>	Manufacturer and reference Milliken "OBEX™ Tile Cut"
<b>Size:</b>	Tile: 5000 x 5000 mm nominal
<b>Colour:</b>	Refer to Finishes schedule
<b>Pattern:</b>	Refer to Finishes schedule
<b>Construction:</b>	Tufted, Cut Pile
<b>Fibre:</b>	ECONYL® regenerated polyamide, twisted and heat set multi/monofilament dual fibres
<b>Backing:</b>	Comfort Lite 90% recycled open cell polyurethane cushion
<b>Yarn:</b>	Twisted and heat-set
<b>Pattern:</b>	Galaxy, Cross, Thread
<b>Finished Dimensions:</b>	<b>Module</b> = 5000 x 5000mm <b>Finished Face Weight</b> = 980 g/m <sup>2</sup> <b>Pile Height</b> = 6.4 mm <b>Total Thickness</b> = 12.0 mm <b>Total Weight</b> = 4,600 g/m <sup>2</sup>
<b>Warranties:</b>	1-Year Manufacturing Defect Warranty 5-Year Wear Warranty
<b>Method of Laying:</b>	By Milliken Approved Contractor. In strict accordance with Milliken installation recommendations.
<b>Special Requirements:</b>	Maintenance method must be demonstrated to ensure not only appearance retention but also to leave OBEX in hygienic condition.