



# Registration Certificate

Carpet Name: **CONSEQUENCE 2.0 - SEQUEL**

Licensee: **MILLIKEN (AUSTRALIA) PTY LTD**

Licence Number: **008**

Label Number: **14151**

ACCS Contract Grading: **CEHD 4\***  
ACCS Residential Grading: **NONE**  
Suitable for Stairs: **Yes**

Date Printed: **14/09/2016**



*Allan Firth*



**Allan Firth**  
Secretary ACCS



**Administered by the Carpet Institute of Australia Limited** ABN 11 006 829 303  
PO Box 7172, St Kilda Road, Melbourne Victoria 8004 Tel: (03) 9804 5559 • Fax: (03) 9804 5560  
Email: [info@carpetoz.com.au](mailto:info@carpetoz.com.au) • [www.carpetinstitute.com.au](http://www.carpetinstitute.com.au)

This certificate remains the property of the Carpet Institute of Australia Limited.

Names:

CONSEQUENCE 2.0 - SEQUEL

Details:

Awarded Res Grade: NONE

Awarded Con Grade: CEHD4\*

Registered On: 24/07/2014

Active: Yes

Date In-Active:

Manufacture Method: Tufted

Twist Set: N/A

Dyeing Method: Melt Dyed

#Colours/Designs: 20

Backing Type: Foam

Felted: N/A

Spinning System: BCF

Insect Resist Agent: N/A

Filament: /

Master Product:

Hexapod Scores:

	Texture		Colour		Thickness	
	WA		WA		(mm)	(%)
1500:	4.5	4.0	4.5	4.5	0.3	7.5
8000:	3.5	3.5	4.0	4.0	0.8	20.0

ACCS Test:

	Con	Res	Max
SPM/PH Ratio:	16	16	16
Volume Density:	20	20	20
Tuft Density:	9	9	9
Dyn Load:	5	5	5
Stat Load:	4	4	5
Soiling Prop:	14	14	16
Abrasion Res:	10	10	10
Sub Total:	78	78	81
Panel Assess:	14	14	19
Total:	92	92	100
Calc Residential Grade:	REHD2		6*
Calc Contract Grade:	CHD		3*

Test Results:

Pile Mass g/m² (oz/yd²): 915 (27.0)

SPM g/m² (oz/yd²): 597 (17.6)

Stated Pile Height (mm): 3.1

Minimum Pile Height (mm): 0.0

Maximum Pile Height (mm): 0.0

Dynamic Loading Loss (%): 15.0

Static Loading Loss (%): 20.0

Tex (g/1000m): 469

Measured Pile Thickness (mm): 4.0

Machine Gauge (Tufts/dm): 39.4

Meas Tufts Perp to Selvedge: 39.9

Meas Tufts Para to Selvedge: 48.0

Treated For Soiling Resistance: Yes

Soil Resist Inhibitor: Yes

Stain Resist Inhibitor: Yes

Quality Assurance Test:

Cut Pile (%): 0

Loop Pile (%): 100

Panel Assessment Contract: 14

Panel Assessment Residential: 14

Suitable For Stairs: Yes

Tile: Yes SheetGoods: No

Fibre Signature: NBA:100

Calculations

Pile Height(mm): 3.4

Tuft Density(per dm²): 1915.2

GSPM(g/m²): 415.0

GSPM (abrasive) (g/m²): 275.0

Soiling Propensity: 12.0 +2.0

OAF Values

OAF: 4.2

Calc Density (+-5%):0.14 0.149 0.16

Base Fibre: NYLON

Benchmarks:

RHD10RHD23.5

REHD13.5REHD23.5

Environmental Classification:

ECS:

Level: 0

Calc

B/M

P/F

Acoustic:

4

3

PASS

Thermal:

26.8

15

PASS

VOC:

TVOC

10

Notes:

23/7/14 Submitted by T Nguyen. 30/7/14 Panel awarded CEHD(S) 4\*. 24/3/15 Deactivated and name CONSEQUENCE 2.0 - SEQUEL removed. 9/5/16 Now under Milliken. 14/9/16 Reactivate as inactivated by Licensee in error.