

# Declare.

---

## Metro Park LVT Milliken

**Final Assembly:** Changzhou, Jiangsu, China

**Life Expectancy:** Commercial: 25 Year(s)

**End of Life Options:** Recyclable (100%)

### Ingredients:

---

Calcium carbonate; Polyvinyl chloride; Di(2-ethylhexyl) terephthalate; Magnesium hydroxide; Polyethylene; Carbon black; Calcium Stearate; Zinc Stearate; Petroleum resins; Benzene, ethenyl-, polymer with 2-methyl-1,3-butadiene; White mineral oil (petroleum); Epoxy Acrylate; 2-Propenoic acid, 1,6-hexanediyl ester; 2-Propenoic acid, (1-methyl-1,2-ethanediyl) bis[oxy(methyl-2,1-ethanediyl)] ester; Octadecanoic acid, 2,3-dihydroxypropyl ester; oxybis(methyl-2,1-ethanediyl) diacrylate; Talc; Trimethylolpropane Triacrylate/2-Hydroxypropyl Acrylate; Silica, amorphous, fumed, cryst.-free; 2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester

### Living Building Challenge Criteria:

---

#### I-13 Red List:

- |  |                             |
|--|-----------------------------|
| <input type="checkbox"/> LBC Red List Free     | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input checked="" type="checkbox"/> Declared   |                             |

**I-10 Interior Performance:** CDPH Standard Method v1.1-2010

**I-14 Responsible Sourcing:** Not Applicable

MKN-0030

EXP. 01 NOV 2023

Original Issue Date: 2019