

Mosaic 98 – Spray

Milliken

SPRAY ADHESIVE

For Mixed Media

Carpet Tile
2 mm, 2.5 mm and 5 mm FlexForm™ LVT
5 mm FlexForm™ Sound LVT*

*Hospitality Rooms only, no public areas, Semi-Wet or WET application required



UP TO 11



UP TO 98%



DRY TIME
10-20 min



WORKING TIME
4 hrs



ROLL FLOOR
within 1 hr (LVT Only)



CURE TIME
less than 1 hr



LIGHT TRAFFIC
Immediate use



HEAVY TRAFFIC
Immediate use



HEAVY ROLLING
LOADS : Immediate Use



22 oz Can
(6 per box)
Spray

Versatile Spray Adhesive for Mixed Media

For use with RH up to **98%**

Installation after new pour: **45 days**



The Benefits of
Milliken Adhesives

Milliken offers adhesive solutions for any scenario:

- Modular carpet, LVT, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required



FLOORING TYPE

Modular Carpet Tile
2 mm, 2.5 mm, 5 mm
FlexForm™ LVT
5 mm FlexForm Sound™
LVT*

*Hospitality rooms only,
no public spaces

ESTIMATED COVERAGE

150-185 sf/can

- Mosaic 98 - Spray provides immediate shear strength following installation to allow instant access to finished flooring
- Instant shear strength also allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads
- Mosaic 98 - Spray is a solvent-free, non-toxic product allowing occupation of spaces immediately following installation

Mosaic 98 – Spray



PRODUCT CHARACTERISTICS	Product Classification	High-moisture spray adhesive
	Base Chemistry	Water-based acrylic blend
	Appearance	Milky white frost bubbles
	Application	Spray
	Flammability	Non-flammable
	Freeze/Thaw	Protect from freezing
	Shelf Life	3 years (unopened)
MOISTURE	RH	98%
	pH	Up to 11
TIME	Dry Time	10-20 mins until dry to touch
	Working Time	4 hrs (after tack)
	Roll & Cross Roll Floor (75- 100lb roller)	Within 1 hour after installation
TRAFFIC	Light Traffic	Immediately
	Heavy Traffic	Immediately
	Heavy Rolling Loads	Immediately
SUSTAINABILITY	Solvents	None
	Total VOCs	0.5 mg/m ³ or less
	Compliant with	California DPH Section 01350 Version 1.2
	Certifications	CRI Green Label Plus

STORAGE This product should be stored at temperatures between 68-95°F indoors (20-35° C). It is necessary to protect this product from freezing.

CAUTION DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY For Milliken installation instructions and warranties, visit millikenfloors.com.

