

WELLBAC® COMFORT - BK9C

Modular Tiles and Planks

| PRODUCT SPECIFICATION | |
|-----------------------------------|---|
| Standard Backing | Cushion Backing WellBAC® Comfort (PVC FREE) (Non-Reactive Cushion Backing) |
| Acoustic Value | Noise Reduction Coefficient - NRC ≥ 0.25 |
| | Impact Sound Pressure Level - Ln,w ≤ 47dB |
| Concrete Slab Moisture Mitigation | Site-Related Solutions (SRS): Milliken cushion-backed tile + Non-Reactive Standard Adhesive means installation 45 days after a new concrete pour, fully warranted no moisture testing required. Refer to www.millikenfloors.com.au |
| Antiviral Antibacterial | MGUARD+ Antiviral and Antibacterial Treatment. For further information refer to www.millikenfloors.com.au |

WELLBAC®
Milliken WellBAC® open cell foam cushion provides superior durability, appearance retention and cushioning.

| | | | | | |
|--|---|--|---|---|---|
| | | | | | |
| UNDERFOOT COMFORT Up to 24% greater underfoot comfort for enhanced ergonomics whilst standing. | ACOUSTIC VALUES Up to 50% improved acoustics for quieter, more productive spaces. | INDOOR AIR QUALITY Enhanced Indoor Air Quality (Green Label Plus™ Certified Low VOC) for improved occupant and installer well-being. | MOISTURE MITIGATION Industry leading moisture management with non-reactive backings to enhance the installation process, saving time and money. | MATERIAL HEALTH 3rd party Verified Declare™ Red-List Free products for occupant and installer well-being. | CIRCULARITY 100% Recyclable through the Milliken N/XT LIFE circularity program for both installation waste and end-of-life. |

| | | | |
|---|--|---|---|
| Construction | Tufted, Texture Loop | Flammability (Radiant Panel Test) | CHF/CRF = 5.2kW/m ² Smoke Value = 182%. min |
| Tile Size | 50cm x 50cm, 25cm x 100cm, 100cm x 100cm | Lightfastness (AATCC 16E) | ≥ 4.0 at 80 Hours |
| Yarn Type | Milliken Certified 100% Nylon | Static Electricity (AATCC-134) 20% R.H., 70° F | ≤ 3.5V |
| Stain Resist Soil Release | StainSmart® | Indoor Air Quality CRI Green Label Plus™ | ≤ 0.5mg/m ³ (GLP0793) |
| Dye Method | PrintWorks™ | VOC | Pass (ISO 10580:2010) |
| Gauge | 1/12 | ACCS Grading | CEHD 4*, REHD2 6*, Suitable for Stairs |
| Stitches Per Inch | 11.2 | Environmental | ECS Grading - Level 4 + (Core + No Chemicals of Concern + EPD + Carbon Neutral) Declare - RED LIST FREE Cradle to Cradle - Silver M/PACT™ Carbon Neutral Program Environmental Product Declaration (EPD) Health Product Declaration (HPD) Works With WELL |
| Tufts | 134/in ² (2,081/100cm ²) | | |
| Recyclable | 100% | | |
| Recycled Content by Total Weight | 46% | | |
| Nominal Total Thickness | 8.2mm | | |
| Nominal Pile Thickness | 2.1mm | | |
| Nominal Total Weight | 92.9 oz/yd ² (3,150g/m ²) | | |

| | | |
|--|--|--|
| The recognised Product Certification Initiatives in the Green Star rating tools that contribute to the responsible product value of Milliken carpet tiles are as listed. The Green Building Council of Australia recognises Responsible Products that may contribute to a Green Star rating through its Responsible Credits (rpv). | <ol style="list-style-type: none"> ECS Carpet Standard v2.2 Cradle to Cradle Declare 2.0 - Red List Free Science-Based Targets Initiative (SBTi) | GBCA Responsible Product Value 30 rpv |
|--|--|--|

| | | | | |
|---|---|------------------------------|--|------------------------------------|
| Recommended Installation Methods | Tiles Planks: Depended on the collection design | | | |
| Recommended Area of Use | Commercial Extra Heavy Duty | | | |
| Warranties | 20-year Wear Warranty | 20-year Anti-Static Warranty | 20-year Dimensional Stability Warranty | 20-year Castor Chair Wear Warranty |



WORKS WITH WELL

Milliken’s commitment to advancing products and solutions that support human health and well-being is long-standing.



As a founding member of the **Well Living Lab** and a **Well Portfolio Member**, we aspire to design products that enhance the well-being and quality of life of indoor spaces.

We are proud to have been granted the **Works with WELL™** licence across an extensive selection of our global product portfolio, demonstrating how Milliken floor covering products align with specific strategies in the WELL Standard, the leading global standard for health and well-being.

The Works with WELL trademark licensing program recognises products and solutions that contribute to achieving specific features in the WELL Standard. Products that have earned the Works with WELL mark have been validated through one or more review cycles to give specifiers the maximum confidence in their material selections, whether working on a WELL-certified project or simply wanting to ensure they are adopting best practices for healthy, sustainable, people-first spaces for their clients.



| CONCEPT | | FEATURE | FEATURE NAME |
|---------|------------------|---------|--|
| | WATER | W07.2 | Design Interiors for Moisture Management |
| | MOVEMENT | V02.4 | Provide Support at Standing Workstations |
| | MATERIALS | X05.2 | Select Compliant Architectural and Interiors Products |
| | | X06.2 | Restrict VOC Emissions from Furniture, Architectural and Interior Products |
| | | X07.1 | Select Products and Disclosed Ingredients |
| | | X07.2 | Select Products with Enhanced Ingredients Disclosure |
| | | X07.3 | Select Products with Third-Party Verified Ingredients |
| | | X08.1 | Select Materials with Enhanced Chemical Restrictions |
| | | X08.2 | Select Optimised Products |

Driven by the global demand for healthier places and healthier organisations that support people to thrive, WELL adoption has grown exponentially since its launch in 2014. WELL strategies have been used in over 5 billion square feet of space, supporting the health and well-being of an estimated 17 million people in more than 74,000 locations spanning over 130 countries.

Contact one of our team of WELL Accredited Professionals for support with your next WELL Certified project at millikenanzesquiries@milliken.com.

