

Milliken® Cable Management Vis™ Tape



VT 1250

1250 lb pull tape in standard, detectable options

Pull tape, made of low friction, high tenacity, abrasion resistant yarns and printed using MPrint™ technology.

Specifications

Tensile Strength	1250 lb (Minimum)
Working Load	1250 lb
Approx. Width	0.50" +/- 0.0625" or 1/16"
Approx. Thickness	0.037" +/- 0.007"
Approx. Weight	6.4 lbs (9.1 lbs DET) per 1,000 feet
Color	White
Print Color	Black

STANDARD SPOOL LENGTHS	VT 1250	VTDET 1250
1,000'	●	
3,000'	●	●
5,000'	●	●
10,000'	●	
100,000'	●	

Features & Benefits

- Pre-lubricated
- Printed with sequential foot markings
- Packaging: UV resistant white plastic wrap
- VTDET: Detectable wire is a 22 ga solid tinned copper conductor, 23 ohms per mile resistance
- Palletized and shrink wrapped: All rolls 3,000' and smaller have 36 spools per pallet; all rolls larger than 3,000' have 27 spools per pallet
 - Pallets are 48x48x60 for 3,000' spools and smaller, 5 layers high.
 - Spools larger than 3,000' -pallets are 48x48x72, 4 layers high.

Metric

Width 12.5 mm +/- 1 mm

Width 0.94 mm +/- 0.2 mm