

SPECIFICATION SHEET DATE: 16/8/2023

MIXED FORMATIONS (FLEXFORM™ LVT)

Made of Stone

Milliken Hybrid Flooring System



When you choose M/PACT™ products, you can be sure your choice is carbon neutral. M/PACT™ carbon neutral products offset the raw materials and manufacturing carbon footprint* by using 3rd party Verified Carbon Standard Credits that support renewable energy and carbon reduction technologies to help fight climate change.

*as calculated and verified through a ISO14025/ISO14040 compliant LCA and published in third party EPD.

Acoustic Value	Impact Sound Pressure Level - Ln,w = 67dB
----------------	---

Construction	High performance
	FLEXFORM™ LVT
Finish	ProGuard™ Reinforced
	Polyurethane Coating
Wear Layer Thickness	0.55mm
Tile Size	18" x 36"
	(45.72cm x 91.44cm)
Overall Thickness	5mm
Edge Profile	Micro Bevel
Recyclable	100%
Pieces Per Box	6 pc (approx. 2.51sqm ² / box)
Weight Per Box	24.52kg
_	
Quantity Per Box	2.51m ²
-	
Environmental	Declare
	Carbon Neutral
	GreenRate by Global Green Tag
	Best Practice PVC
	Environmental Product
	Declaration (EPD)

Critical Radiant Flux	10.4kW/m²
Smoke Rate	115%.min
Use Classification (ISO 10582)	Class 33 Heavy Duty Commercial
Slip Resistance Classification	P3 and R10
Heat Stability of Colour Change (ASTM F1514)	PASS
Light Stability (ASTM F1515)	PASS
Static Coefficient of Friction (ASTM D2047)	PASS
Determination of Dimensional Stability & Curling after Exposure to Heat (ISO 23999)	≤0.25%; Curl ≤2mm
Resistance to Chemicals (ASTM F925)	PASS
Residual Indentation (ISO 24343-1)	≤0.1mm
Static Load Limit (ASTM F970)	PASS
Castor Chair Resistance (ISO 4918)	PASS
Flexibility (ISO 24344)	PASS

Recommended Installation Method(s)	Glue Down
Recommended Area of Use	Commercial Residential
Warranties	15-year Wear Warranty
	15-year Heavy Commercial Warranty















Milliken Hybrid Flooring System is highly durable resilient flooring engineered with the highest quality raw materials to provide unsurpassed performance and enduring aesthetics.

Milliken Hybrid Flooring System is 100% ortho-phthalate-free.

Milliken Hybrid Flooring System is manufactured at facilities that are ISO 9001 and ISO 14001 compliant.