## SANDHILLS (WELLBAC® COMFORT - ORG18)

Sandhills | Safari | Passage | Cavern | Rainforest | Bush Seed

## Milliken

Modular Tiles and Planks

| Sandhills   Safari   Passage   Cavern   Rainforest   Bush Seed   |  |  |   |  |  |                               | Modular Tiles and Plank   |   |  |  |
|--|--|--|---|--|--|-------------------------------|---|---|--|--|
| PRODUCT SPECIFI  | CATION   |  |   |  |  |                               |   |   |  |  |
| Standard Backing   | Cushion Backing   WellBAC <sup>®</sup> Comfort (PVC FREE) (Non-Reactive Cushion Backing) |  |   |  |  |                               |   |   |  |  |
| Acoustic Value   |  |  | Noise Reduction   | Noise Reduction Coefficient - NRC $\geq 0.25$  |  |                               |   |   |  |  |
|  |  |  | Impact Sound Pressure Level – Ln,w ≤ 47dB   |  |  |                               |   |   |  |  |
|  |  |  | installation 45 da  | Site-Related Solutions (SRS): Milliken cushion-backed tile + Non-Reactive Standard Adhesive means installation 45 days after a new concrete pour, fully warranted no moisture testing required. Refer to www.millikenfloors.com.au |  |                               |   |   |  |  |
|  |  |  | MGUARD+ Antiviral and Antibacterial Treatment. For further information refer to<br>www.millikenfloors.com.au                    |  |  |                               |   |   |  |  |
| Λ  | 1illiken WellBA  | C® open cel  |   |  | <b>_BAC®</b><br>uperior durability, app  | earance reter                 | ntion and cushion   | ing.  |  |  |
|  |  |  |   |  |  |                               |   |   |  |  |
| UNDERFOOT COMFORT<br>Up to 24% greater underfoot<br>comfort for enhanced<br>ergonomics whilst standing.  | ACOUSTIC<br>Up to 50% i<br>acoustics fo<br>more product                                  | improved<br>r quieter,   | INDOOR AIR QUAL<br>Enhanced Indoor Air Q<br>(Green Label Plus<br>Certified Low VOC)<br>improved occupant<br>installer well-bein | uality<br>™<br>for<br>and  | MOISTURE MITIGATIO<br>Industry leading moistu<br>management with non<br>reactive backings to enha<br>the installation process, sa<br>time and money. | ire 3<br>I- Dec<br>ince produ | ATERIAL HEALTH<br>ird party Verified<br>lare™ Red-List Free<br>ucts for occupant and<br>staller well-being.                     | CIRCULARITY<br>100% Recyclable through the<br>Milliken N/XT LIFE circularity<br>program for both installation<br>waste and end-of-life. |  |  |
| Construction Tufted, Te:   |  | ture Loop  |   | ,  |  |                               | CHF/CRF = 7.5kW/m <sup>2</sup><br>Smoke Value = 173%. min   |   |  |  |
| Tile Size  |  | 50cm x 50cm,   |   |  | Lightfastness (AATCC 16E)  |                               | $\geq$ 4.0 at 80 Hours  |   |  |  |
| Yarn Type  |  | 25cm x 100cm, 1m x 1m<br>Milliken Certified<br>100% Nylon                                      |   |  | Static Electricity (AATCC-134)<br>20% R.H., 70° F  |                               | ≤3.5V   |   |  |  |
|  |  | StainSmar  |   |  | Indoor Air Quality CRI Green<br>Label Plus™  |                               | ≤ 0.5mg/m <sup>3</sup> (GLP0793)  |   |  |  |
| Dye Method PrintWorks  |  | STM  |   | VOC  |  | Pass (ISO 10580:2010)         |   |   |  |  |
| Gauge<br>Stitches Per Inch   |  | 1/12   |   |  | ACCS Grading<br>Environmental  |                               | CEHD 4*, REHD2 6*, Suitable for Stairs<br>ECS Grading – Level 4 + (Core +<br>No Chemicals of Concern + EPD +<br>Carbon Neutral) |   |  |  |
| Tufts<br>Total Pile Mass   |  | 132/in <sup>2</sup> (2,044/100cm <sup>2</sup> )<br>18oz/yd <sup>2</sup> (610g/m <sup>2</sup> ) |   |  |  |                               | Declare - RED LIST FREE<br>Cradle to Cradle - Silver  |   |  |  |
|  |  | 1002/yu (  |   |  |  |                               | M/PACT <sup>™</sup> Carbon Neutral Program  |   |  |  |
| Recycled Content by Total Weight   |  | 44%  |   | -  |  |                               | Environmental Product Declaration (EPI  |   |  |  |
|  |  | 8.5mm<br>3.0mm   |   |  |  |                               | Health Product Declaration (HPD)<br>Works With WELL   |   |  |  |
|  | Total Weight   |  | (3,251g/m <sup>2</sup> )  |  |  |                               |   |   |  |  |
| The recognised Product Certification Initiatives in the Green<br>tools that contribute to the responsible product value of Mil<br>tiles are as listed. The Green Building Council of Australia re<br>Responsible Products that may contribute to a Green Star ra<br>through its Responsible Credits (rpv). |  |  | ue of Milliken carpe<br>stralia recognises  | f Milliken carpet 2. Cradle to Cradle<br>lia recognises 3. Declare 2.0 - Red List Free   |  |                               | GBCA<br>Responsible Product Value<br>30 rpv   |   |  |  |
| Installati   | commended<br>ion Methods   | Passage, R<br>Sandhills, I   | Passage, Rainforest   | shlar (<br>(1m x 1   | (Tile): Monolithic<br>Vertical)   Herringbon<br>1m Rug): Monolithic  | le                            |   |   |  |  |
| Recommended Area of Use<br>Warranties  |  | Commercial Extra Heavy Duty<br>20-year   |   | /  | 20-year 20-yea   |                               | r Dimensional 20-year Castor Chair  |   |  |  |
|  |  |  |   |  |  |                               |   |   |  |  |



## WORKS WITH WELL

Milliken's commitment to advancing products and solutions that support human health and well-being is long-standing.

As a founding member of the **Well Living Lab** and a **Well Portfolio Member**, we aspire to design products that enhance the well-being and quality of life of indoor spaces.



We are proud to have been granted the **Works with WELL™** licence across an extensive selection of our global product portfolio, demonstrating how Milliken floor covering products align with specific strategies in the WELL Standard, the leading global standard for health and well-being.

| The Works with WELL trademark licensing program recognises products and solutions that contribute to achieving specific features in the WELL Standard. Products that have earned the Works with WELL mark have been validated through one or more review cycles to give specifiers the maximum confidence in their material selections, whether working on a WELL-certified project or simply wanting to ensure they are adopting best practices for healthy, sustainable, people-first spaces for their clients. |           |         |  |  |  |  |  |  |
|---|-----------|---------|--|--|--|--|--|--|
| CONCEPT   |           | FEATURE | FEATURE NAME   |  |  |  |  |  |
|   | WATER     | W07.2   | Design Interiors for Moisture Management                                   |  |  |  |  |  |
| S   | MOVEMENT  | V02.4   | Provide Support at Standing Workstations                                   |  |  |  |  |  |
|   |           | X05.2   | Select Compliant Architectural and Interiors Products                      |  |  |  |  |  |
|   | MATERIALS | X06.2   | Restrict VOC Emissions from Furniture, Architectural and Interior Products |  |  |  |  |  |
|   |           | X07.1   | Select Products and Disclosed Ingredients                                  |  |  |  |  |  |
|   |           | X07.2   | Select Products with Enhanced Ingredients Disclosure                       |  |  |  |  |  |
|   |           | X07.3   | Select Products with Third-Party Verified Ingredients                      |  |  |  |  |  |
|   |           | X08.1   | Select Materials with Enhanced Chemical Restrictions                       |  |  |  |  |  |
|   |           | X08.2   | Select Optimised Products  |  |  |  |  |  |
| (djo)   | MIND      | M02.1   | Provide Connection to Nature   |  |  |  |  |  |

Driven by the global demand for healthier places and healthier organisations that support people to thrive, WELL adoption has grown exponentially since its launch in 2014. WELL strategies have been used in over 5 billion square feet of space, supporting the health and well-being of an estimated 17 million people in more than 74,000 locations spanning over 130 countries.

Contact one of our team of WELL Accredited Professionals for support with your next WELL Certified project at <u>millikenanzenquiries@milliken.com</u>.

