

## M50 CARPET TILING

130	Carpet Body Tiles
Location:	Refer to Finishes Schedule
Preparation:	According to the guidelines laid out in the Contract Flooring Association's "Guide to Contract Flooring".
Carpet Tiles:	Manufacturer and reference Milliken "Consequence 2.0 - Effect, Part Two, React, Sequel, Spin Off, Upshot - Tile"
Size:	500 x 500mm nominal to be die cut for consistent tolerance.
Colour:	Refer to Finishes schedule
Pattern:	Refer to Finishes schedule
Construction:	Tufted Luxury Textured Loop Pile
Fibre:	100% Nylon 6 including 40% ECONYL made with 100% regenerated fibre Chosen for soil hiding and resilience.
Backing:	High-density, open-cell polyurethane foam. 90% recycled Improved comfort, acoustics and wear performance.
Yarn:	Spun yarn, heat set.
Pattern:	Effect, Part Two, React, Sequel, Spin Off, Upshot
Finished Dimensions:	Module = 500 x 500mm Pile Weight = 915 g/m <sup>2</sup> Pile Height = 5.6mm Tuft Density = 226, 088 per m <sup>2</sup> Total Thickness = 11.8 mm Total Weight = 4630 g/m <sup>2</sup>
Warranties:	15 year wear warranty Lifetime Antistatic Latent Defects
Method of Laying:	By Milliken Approved Contractor. In strict accordance with Milliken installation recommendations.
Special Requirements:	Maintenance method must be demonstrated to ensure not only appearance retention but also to leave carpet in hygienic condition.