NORTHWARD BOUND WellBAC® Function Plus

Glacier

Construction	Tufted, Textured Loop Pile
Face Fibre	Thrive Matter 90% recycled Nylon
Stain Resist	Inherently stain resistant fibre
Finished Face Weight	495 g/m^2
Gauge	47.2 / 10 cm
Rows	37.5 / 10 cm
Tuft Density	177,165 /m^2
Finished Pile Height	2.8 mm
Standard Backing	WellBAC® Function Plus Polymer modified bitumen hard back
Nominal Total Thickness	5.9 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	3800 g/m^2
Tiles per Box	22 (5.5m^2)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2018)	Class Bfl – s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A – Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	22 dB ΔL_w
Sound Absorption (ISO354)	0.15 Class E (estimated)
Alpha p values	Est.-125Hz 0.00, 250Hz 0.00, 500Hz 0.05, 1000Hz 0.15, 2000Hz 0.35, 4000Hz 0.40

ENVIRONMENTAL

66% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors,
6.50 kg CO_2 e/m^2 Embodied Carbon (EPD calculation A1-A3)
Cradle to Gate footprint 100% off set

WARRANTIES

10 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

INSTALLATION

Monolithic

CE / UKCA

DOP-2895-1004-02 BS EN 14041:2018

DOP-0338-1004-02 BS EN 14041:2018

Design Copyright – Milliken & Company.
Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.