

AMPLIFIER (WellBAC® Function)

Beats | Echo

Modular Tiles

M/PACT™

CARBON NEUTRAL PROGRAM

When you choose M/PACT™ products, you can be sure your choice is carbon neutral. M/PACT™ carbon neutral products offset the raw materials and manufacturing carbon footprint* by using 3rd party Verified Carbon Standard Credits that support renewable energy and carbon reduction technologies to help fight climate change.

*as calculated and verified through a ISO14025/ISO14040 compliant LCA and published in third party EPD.

WELLBAC®

Milliken WellBAC® open cell foam cushion provides superior durability, appearance retention and cushioning.

Up to 24% greater underfoot comfort for enhanced ergonomics whilst standing.

Up to 50% improved acoustics for quieter, more productive spaces.

Industry leading moisture management with non-reactive backings to enhance the installation process.

3rd party Verified Red-List Free products for occupant and installer well-being.

Enhanced Indoor Air Quality (Low VOC) for improved occupant and installer well-being.

Standard Backing	WellBAC® Function (PVC FREE) (Non-Reactive Backing)
Acoustic Value	Noise Reduction Coefficient - NRC ≥ 0.20 Impact Sound Pressure Level - Ln,w ≤55dB

Construction	Tufted, Textured Loop	Flammability (Radiant Panel Test)	CHF/CRF = 4.7kW/m ² , Smoke value = 114%.min
Tile Size	50cm x 50cm	Lightfastness (AATCC 16E)	> 4.0 at 80 Hours
Yarn Type	100% Solution Dyed Nylon	Static Electricity (AATCC-134) 20% R.H., 70° F	≤ 3.5KV
Stain Resist Soil Release	Built-In Protection	Indoor Air Quality CRI Green Label Plus™	≤0.5mg/m ³ (GLP3200)
Dye Method	Solution Dyed	VOC	Pass (ISO 10580:2010)
Gauge	1/12	ACCS Grading	CHD 3*, REHD2 6*, Suitable for Stairs
Stitches Per Inch	10	Environmental	ECS Grading - Level 4 (Certificate No. 18006)
Tufts	120/in ² (1,858/100cm ²)		Declare - 3 rd Party Verified RED LIST FREE
Recyclable	100%		Cradle to Cradle - Silver
Nominal Total Thickness	5.60mm		Carbon Neutral
Nominal Pile Thickness	2.79mm		Environmental Product Declaration (EPD)
Nominal Total Weight	102.5 oz/yd ² (3,476 g/m ²)		Health Product Declaration (HPD)

Recommended Installation Method(s)	Beats, Echo: Quarter Turn Monolithic Echo: Random
Recommended Area of Use	Commercial Heavy Duty
Warranties	15-year Wear Warranty
	15-year Dimensional Stability Warranty
	15-year Anti-Static Warranty
	15-year Castor Chair Wear Warranty



Alliance
Founding
Member

