

Declare.

WellBAC Comfort Carpet Tile - US Milliken

Final Assembly: LaGrange, Georgia, USA

Life Expectancy: 15 Year(s)

End of Life Options: Recyclable (100%)

Ingredients:

Calcium Carbonate; Nylon 6; Nylon 6,6; Polyurethane; Polypropylene; POLYETHYLENE TEREPHTHALATE/POLYBUTYLENE TEREPHTHALATE; Asphalt; Carbonic acid, magnesium salt (1:1); Acetic acid ethenyl ester, polymer with ethene; Polymer; Glass Fiber; POLYCAPROLACTAM THERMOPLASTIC RESIN; Hydrocarbons, C6-20, polymers, hydrogenated; Amorphous Quartz; Chromate(3-), bis[3-hydroxy-4-[(2-hydroxy-1-naphthalenyl)azo]-7-nitro-1-naphthalenesulfonato (3-)-], trisodium; Ethanol, 2-(2-butoxyethoxy)-; 2-Propenoic acid, polymer with 1-propene; Salt of polycarboxylic acid; Carbon black; Titanium dioxide; Glycerin-Kokos÷I-Transester-EO/PO-random, (mittlere Molmasse 1000 g/mol); Amides, C8-18 and C18-unsatd., N,N-bis(hydroxyethyl); Acid Yellow 199; Anthra[2,1,9-def:6,5,10-d'e'f'] diisoquinoline-1,3,8,10(2H,9H)-tetrone, 2,9-bis(3,5-dimethylphenyl)-; Bismuth vanadium oxide; C. I. Pigment Blue 15; C.I. Pigment Brown 24; C.I. Pigment Green 7; Chromate(3-), [3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-2-hydroxy-5-nitrobenzenesulfonato (3-)] [3-hydroxy-4-[(2-hydroxy-1-naphthalenyl)azo]-7-nitro-1-naphthalenesulfonato(3-)-], sodium; Iron Oxide; Pigment Violet 23; Sodium Hydroxide; Stearic Acid; Diethanolamine; Caprolactam; Alcohols, C12-14, ethoxylated; Acetic acid ethenyl ester, polymer with ethenol; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Poly(oxy-1,2-ethanediyl), α -[4-(1-phenylethyl)phenyl]- ω -hydroxy-; N,N'-bis(2,2,6,6-tetramethyl-4-piperidyl)isophthalamide; Dodecansuremethylester, ethoxyliert, EO 6 bis 15 mol; Amylopectin, 2-hydroxy-3-(trimethylammonio)propyl ether, chloride; Fatty acids, coco, esters with trimethylolpropane; Fatty acids, C16-18 and C18-unsatd., branched and linear, ethoxylated; Distillates (petroleum), hydrotreated middle; Benzene, C10-13-alkyl derivs.; Castor oil, hydrogenated, ethoxylated; Siloxanes and Silicones, di-Me, hydroxy-terminated, ethoxylated propoxylated; Poly(oxy-1,2-ethanediyl), α -(1-oxo-9-octadecenyl)- ω -[(1-oxo-9-octadecenyl)oxy]-, (Z,Z)-; Phosphinic acid, phenyl-; Sulfuric acid, mono-C10-16-alkyl esters, ammonium salts; Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester; Poly(oxy-1,2-ethanediyl), α -(1-oxo-9-octadecenyl)- ω -hydroxy-, (Z)-; Poly(oxy-1,2-ethanediyl), α -tridecyl- ω -hydroxy-, phosphate, potassium salt; Butene, polymer with ethene; Poly(oxy-1,2-ethanediyl), alpha-phosphono-omega-(dodecyloxy)-, compd. with 2,2'-iminobis[ethanol], (EO 2-8 mol); Octadecanoic acid, 2-methylpropyl ester

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: Not Applicable
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

MKN-0027
EXP. 01 APR 2026
Original Issue Date: 2018

Third
Party
Verified