SPECIFICATION SHEET Date: 8.11.2021 Revision 8

## **FACET**

Facet / Facet Accents / Facet Transitions



Construction	Tufted, Level Loop Pile
Face Fibre	Nylon 6
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	420 g/m <sup>2</sup>
Gauge	39.4 / 10 cm
Rows	56 / 10 cm
Tuft Density	220,472 /m²
Finished Pile Height	3.0 mm
Finished Pile Height Standard Backing	3.0 mm  Comfort Lite 90% Recycled Open Cell Polyurethane Cushion Backing
	Comfort Lite 90% Recycled Open Cell Polyurethane
Standard Backing	Comfort Lite 90% Recycled Open Cell Polyurethane Cushion Backing
Standard Backing Nominal Total Thickness	Comfort Lite 90% Recycled Open Cell Polyurethane Cushion Backing 8.9 mm
Standard Backing  Nominal Total Thickness  Tile Size	Comfort Lite 90% Recycled Open Cell Polyurethane Cushion Backing 8.9 mm 50 cm x 50 cm

PERFORMANCE	
Flammability (Euroclassification EN13501:1-2018)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	30 dB
Sound Absorption (ISO354)	0.30 Class D
Alpha s values	125Hz 0.00, 250Hz 0.05, 500Hz 0.35, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.40

## **ENVIRONMENTAL**

60% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors, 6.86 kg  $\rm CO_2$  e/m² Embodied Carbon (EPD calculation A1-A3) Cradle to Gate footprint 100% off set

## **WARRANTIES**

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS www.millikenfloors.com/gb/tech										gb/tech			
<b>3</b>	(K Z)							Si S	bsi. ISO 9001:2015 Quality Polassgereat	bsi iso isoooi Sugar Parageneeti	BRE/Global Verified ELS		
CRI CRISTON	GUT.	A+ A B C	PROFI	EPD (France)	WASSION CLASS SAN ON CLASS SAN								



