

OBEX™ TILE: CUTX

SPECIFICATION SHEET DATE: 18 JUNE 2021

MODULAR TILE

Construction Tufted, Cut Pile	Nominal Total Thickness 12.7 mm	Static Electricity (AATCC-134) 20% R.H., 70°F ≤ 3.5 KV, Permanent Conductive Fiber
Tile Size 50 cm x 50 cm	Nominal Total Weight 4,238 g/m ²	Recommended Maintenance Daily Vacuum and Deep Clean with Hot Water Extraction
Textile Yarn Type Milliken-Certified WearOn® Nylon and Monofilament Type 6 and 6, 6	Standard Backing PVC-Free WellBAC™ Comfort Plus Cushion (Available with TractionBack™)	Indoor Air Quality - CRI Green Label Plus™ GLP0793, Carpet Category 5Y
Dye Method Print	Recycled Content by Total Weight 37.5% Pre-Consumer 0.0% Post-Consumer	Recommended Installation Method(s) Monolithic, Quarter-Turn, Ashlar
Tufted Face Weight 949 g/m ²	Flammability (Radiant Panel Test) CHF: 5.5 kW/ m ² Smoke Value: 332 %.min	12 Tiles per box (3 m²)
Gauge 5/32	Lightfastness (AATCC 16E) ≥ 4.0 at 80 Hours	
Stitches Per Inch 9.5	Crocking (AATCC 165) ≥ 4.0 at 80 Hours	
Tufts 942/100 cm ²		
Finished Pile Height 4.72 mm		

Warranties

5 Year Face Fiber Wear	Lifetime Cushion Resiliency	Lifetime Tufted Bind
Lifetime Antistatic	Lifetime Moisture Resistance	Lifetime Edge Ravel
Lifetime Floor Compatibility	Lifetime Delamination of Backing	Flammability
Lifetime Color Pattern Permanency	Lifetime Floor Release	Lifetime Dimensional Stability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.