

Declare.

Fortify Foundations 5.0 Milliken

Final Assembly: Zhenjiang, Jiangsu, China

Life Expectancy: Commercial: 10 Years, Residential: 25 Year(s)

End of Life Options: Recyclable (100%)

Ingredients:

Calcium carbonate; **Polyvinyl chloride**; Octadecanoic Acid, 10-Chloro-9-Methoxy, Methyl Ester; Dioctyl terphthalate, DOTP; Magnesium hydroxide; Glass Fiber; Soybean oil, epoxidized; Calcium Stearate; Zinc Stearate; Carbon black; Epoxy Acrylate; Hexamethylene Diacrylate; 2-hydroxyethyl Methacrylate; 2-Propenoic acid, (1-methyl-1,2-ethanediyl) bis[oxy(methyl-2,1-ethanediyl)] ester; Dipropylene Glycol Diacrylate; Propoxylated neopentyl glycol Diacrylate; Trimethylolpropane Triacrylate; 2,4,6-trimethyl benzoyl diphenyl phosphine oxide; 2-hydroxy-2-methyl-phenyl-propan-1-one

Living Building Challenge Criteria:

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: Not Applicable
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

MKN-0028

EXP. 01 APR 2024

Original Issue Date: 2018