

## Juxtapose - Brights, Neutrals Tile

### M50 CARPET TILING

<b>130</b>	Carpet Body Tiles
<b>Location:</b>	Refer to Finishes Schedule
<b>Preparation:</b>	According to the guidelines laid out in the Contract Flooring Association's "Guide to Contract Flooring".
<b>Carpet Tiles:</b>	Manufacturer and reference Milliken "Juxtapose -Brights, Neutrals Tile"
<b>Size:</b>	500 x 500mm nominal to be die cut for consistent tolerance.
<b>Colour:</b>	Refer to Finishes schedule
<b>Pattern:</b>	Refer to Finishes schedule
<b>Construction:</b>	Tufted Level Loop Pile
<b>Fibre:</b>	Solution Dyed Type 6 6 Nylon Chosen for soil hiding and resilience.
<b>Backing:</b>	High-density, open-cell polyurethane foam. 90% recycled Improved comfort, acoustics and wear performance.
<b>Yarn:</b>	Spun yarn, heat set.
<b>Pattern:</b>	Brights, Neutrals,
<b>Finished Dimensions:</b>	<b>Module</b> = 500 x 500mm <b>Pile Weight</b> = 690 g/m <sup>2</sup> <b>Pile Height</b> = 5mm <b>Tuft Density</b> = 210,000 per m <sup>2</sup> <b>Total Thickness</b> = 10.7 mm <b>Total Weight</b> = 3990 g/m <sup>2</sup>
<b>Warranties:</b>	15 year wear warranty Lifetime Antistatic Latent Defects
<b>Method of Laying:</b>	By Milliken Approved Contractor. In strict accordance with Milliken installation recommendations.
<b>Special Requirements:</b>	Maintenance method must be demonstrated to ensure not only appearance retention but also to leave carpet in hygienic condition.