



# Adhesives

# LVT




ADHESIVE TYPE	RH LEVEL	ADHESIVE	LVT TYPE
<b>TROWEL</b> 	up to 95%	<b>LVT Standard</b> <ul style="list-style-type: none"> <li>For on-grade installations vapor retarder required</li> <li>Approved for all grade renovations where concrete pH levels are between 5-12 and RH is less than 95%</li> </ul> <b>INSTALL</b> 45 days after new pour with RH testing	2 mm, 2.5 mm & 5 mm FlexForm™ LVT
	over 95%	<b>LVT Moisture XT</b> <ul style="list-style-type: none"> <li>Unlimited Moisture Protection</li> <li>NO moisture or PH testing required</li> <li>NO moisture vapor barrier required</li> <li>NO RH, PH, or MVER limits</li> </ul> <b>INSTALL</b> 45 days after new pour / NO moisture testing required	2 mm, 2.5 mm, 5 mm FlexForm™ LVT
<b>SPRAY</b> 	up to 98%	<b>Mosaic 98 - Spray</b> <ul style="list-style-type: none"> <li>Approved for all grade renovations where concrete pH levels are between 5-11 and RH is equal to or less than 98%.</li> </ul> <b>INSTALL</b> 45 days after new pour with RH testing	2 mm, 2.5 mm, 5 mm FlexForm™ LVT  5 mm FlexForm Sound™ LVT*  <i>*Hospitality Rooms only, no public areas</i>
	over 98%	<b>Mosaic Moisture XT-Spray</b> <ul style="list-style-type: none"> <li>For use where very high moisture is a concern.</li> <li>NO moisture testing is required.</li> <li>NO RH or pH limits.</li> </ul> <b>INSTALL</b> 45 days after new pour / NO testing required	5 mm FlexForm™ LVT
<b>TROWEL</b> 	up to 95%	<b>Mosaic 95</b> <ul style="list-style-type: none"> <li>Approved for all grade renovations where concrete pH levels are between 5-11 and RH is equal to or less than 95%</li> </ul> <b>INSTALL</b> 45 days after new pour with RH testing	5 mm FlexForm™ LVT  5 mm FlexForm Sound™ LVT

ADHESIVE TYPE	RH LEVEL	ADHESIVE	FOR
<p><b>ROLL-ON/ TROWEL*</b></p>  <p><i>*Roll-On for carpet tile only Trowel for LVT only</i></p>	<p>up to 95%</p>	<p><b>Mosaic 95</b></p> <ul style="list-style-type: none"> <li>Approved for all grade renovations where concrete pH levels are between 5-11 and RH is equal to or less than 95%</li> </ul> <p><b>INSTALL</b> 45 days after new pour with RH testing</p>	<p>Carpet Tile</p> <ul style="list-style-type: none"> <li>5 mm FlexForm™ LVT</li> <li>5 mm FlexForm Sound™ LVT</li> </ul>
<p><b>SPRAY</b></p> 	<p>up to 98%</p>	<p><b>Mosaic 98 - Spray</b></p> <ul style="list-style-type: none"> <li>Approved for all grade renovations where concrete pH levels are between 5-11 and RH is equal to or less than 98%.</li> </ul> <p><b>INSTALL</b> 45 days after new pour with RH testing</p>	<p>Carpet Tile</p> <ul style="list-style-type: none"> <li>2 mm, 2.5 mm, 5 mm FlexForm™ LVT</li> <li>5 mm FlexForm Sound™ LVT*</li> </ul> <p><i>*Hospitality Rooms only, no public areas</i></p>
	<p>over 98%</p>	<p><b>Mosaic Moisture XT-Spray</b></p> <ul style="list-style-type: none"> <li>For use where very high moisture is a concern.</li> <li>NO moisture testing is required.</li> <li>NO RH or pH limits.</li> </ul> <p><b>INSTALL</b> 45 days after new pour / NO testing required</p>	<p>Carpet Tile</p> <ul style="list-style-type: none"> <li>5 mm FlexForm™ LVT</li> </ul>

# Adhesives

# Modular Carpet



ADHESIVE TYPE	RH LEVEL	ADHESIVE
<p><b>ROLL-ON/ TROWEL</b></p> 	<p><b>NO limit</b> for new construction &amp; above-grade renovations</p> <p><b>95%</b> for on-grade renovations</p>	<p><b>Non-Reactive Standard</b></p> <ul style="list-style-type: none"> <li><b>NEW CONSTRUCTION:</b> Approved for all new construction installations with NO pH or RH limits</li> </ul> <p><b>INSTALL</b> 60 days after new pour with RH testing</p> <ul style="list-style-type: none"> <li><b>RENOVATION:</b> Above-grade renovations: NO pH or RH limits / On-grade renovations (without vapor retarder): RH of 95%, NO pH limit</li> </ul>
<p><b>SPRAY</b></p> 	<p><b>over 98%</b></p>	<p><b>Mosaic Moisture XT-Spray</b></p> <ul style="list-style-type: none"> <li><b>NEW CONSTRUCTION:</b> Approved for all new construction installations with no pH or RH limits</li> </ul> <p><b>INSTALL</b> 30 days after new pour / NO testing required</p> <ul style="list-style-type: none"> <li><b>RENOVATION:</b> Approved for all renovation installations with no pH or RH limits</li> </ul>
<p><b>ADHESIVE-FREE</b></p>  <p><b>Milliken TractionBack®</b></p>	<p><b>NO limit</b> for new construction</p> <p><b>85%</b> for on-grade renovations</p>	<p><b>TractionBack®</b></p> <ul style="list-style-type: none"> <li><b>NEW CONSTRUCTION:</b> Approved for all new construction installations with no pH or RH limits</li> <li><b>NO pH or RH testing required</b></li> </ul> <p><b>INSTALL</b> 90 days after new pour</p> <ul style="list-style-type: none"> <li><b>RENOVATION:</b> Above-grade renovations: NO pH or RH limits / On-grade renovations: RH of 85%, no pH limit</li> </ul>
	<p><b>NO limit</b></p>	<p><b>TractionBack® Plus</b></p> <ul style="list-style-type: none"> <li><b>NEW CONSTRUCTION/RENOVATION:</b> Approved for all installations with NO pH or RH limits</li> </ul> <p><b>INSTALL</b> 30 days after new pour (new construction)</p>