

# Mosaic Moisture XT Spray

Milliken

SPRAY ADHESIVE

## For Mixed Media

Carpet Tile  
5 mm FlexForm™ LVT



NO LIMIT



NO LIMIT



DRY TIME  
10-20 min



WORKING TIME  
4 hrs



ROLL FLOOR  
within 1 hr (LVT Only)



LIGHT TRAFFIC  
Immediate use



HEAVY TRAFFIC  
Immediate use



HEAVY ROLLING  
LOADS : Immediate Use



22 oz Can  
(6 per box)  
Spray

## Extreme Moisture Spray Adhesive

For use with RH up to **No RH Limit**

NO pH or RH limits.  
NO TESTING REQUIRED.

Installation after new pour: **45 days** **CARPET ONLY 30 Days**



The Benefits of  
Milliken Adhesives

Milliken offers adhesive solutions for any scenario:

- Modular carpet, LVT, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required



FLOORING TYPE  
5 mm FlexForm™ LVT  
Modular Carpet Tile

ESTIMATED COVERAGE  
100-125 sf/can

- Mosaic Moisture XT Spray provides immediate shear strength following installation to allow instant access to finished flooring
- Instant shear strength also allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads
- Mosaic Moisture XT Spray is a solvent-free, non-toxic product allowing occupation of spaces immediately following installation

# Mosaic Moisture XT Spray



PRODUCT CHARACTERISTICS	Product Classification	Extreme-moisture spray adhesive
	Base Chemistry	Water-based acrylic blend
	Appearance	Milky white frost bubbles
	Application	Spray
	Flammability	Non-flammable
	Freeze/Thaw	Protect from freezing
	Shelf Life	3 years (unopened)
MOISTURE	RH	No limit
	pH	No limit
TIME	Dry Time	10-20 mins until dry to touch
	Working Time	4 hrs (after tack)
	Roll & Cross Roll Floor (75- 100lb roller)	Within 1 hour after installation
TRAFFIC	Light Traffic	Immediately
	Heavy Traffic	Immediately
	Heavy Rolling Loads	Immediately
SUSTAINABILITY	Solvents	None
	Total VOCs	0.5 mg/m <sup>3</sup> or less
	Compliant with	California DPH Section 01350 Version 1.2
	Certifications	CRI Green Label Plus

**STORAGE** This product should be stored at temperatures between 68-95°F indoors (20-35° C). It is necessary to protect this product from freezing.

**CAUTION** DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

**WARRANTY** For Milliken installation instructions and warranties, visit [millikenfloors.com](http://millikenfloors.com).

