

# CONTINUATION

Construction	High Performance Woven Design Tile
Face Construction	Vinyl with glass fibre core reinforcement
Backing Construction	Flexform Sound™ enhanced acoustic backing
Overall Thickness	5.2 mm
Product Weight	3200 g/m <sup>2</sup>

## PERFORMANCE

Flammability/Smoke Emissions (EN 13501-1)	Class Bfl-s1
Use Classification (EN I307)	Class 33 Heavy Commercial
Dimensional Stability (EN 986)	≤0.20 %
Resistance to Fraying (EN 1814)	Very Good
Colour Fastness to Light (EN ISO 105-B02)	≥7
Castor Chair Resistance (EN 985)	Intensive Use
Stain Resistance (EN432)	Very Good
Electrostatic Performance (EN 1815)	≤2 kV
Impact Sound Reduction (ISO 10141-1)	≤22 dB Δw
Walking Sound on Floors (EN 16205)	≤67 dB (A)
Slip Resistance (DIN 51130) (Ramp)	≤R9
Slip Resistance (EN 13983)	>0.3

## INSTALLATION

Full spread of tackifier adhesive

## ENVIRONMENTAL

13% recycled content by total product weight  
(Pre Consumer internal waste)

Manufactured in ISO14001 certified location

M/PACT Carbon Neutral Floors,  
7.30 kg CO<sub>2</sub> e/m<sup>2</sup> Embodied Carbon (EPD calculation A1-A3)  
Cradle to Gate footprint 100% off set

Orthophthalate and REACH SVHC free- compliant to WELL feature  
requirement for Enhanced Material Restrictions

## WARRANTIES

10 year wear warranty

## TILE SIZE

50cm x 50cm

## TILES PER BOX

16 (4m<sup>2</sup>)

## CERTIFICATIONS

--	--	--	--	--	--	--	--	--	--	--	--

## INSTALLATION



Monolithic

## CE



Design Copyright – Milliken & Company.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.