

1. IDENTIFICATION

MILLIKEN MOISTURE XT w/ACOUSTILOC TECHNOLOGY

Recommended use of the chemical and restriction on use:
Moisture vapor barrier adhesive for installation of flooring materials over approved subfloor –all types of resilient flooring including vinyl, rubber, fiberglass and polyolefin backed flooring.

Company: Milliken Floors

924 Milliken Rd, Spartanburg, SC 29303

Emergency Telephone Number: 800.528.8453

Other Means of Identification

Chemical Family: Modified Silane blend

2. HAZARDS IDENTIFICATION

According to regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

Classification of the Product

No need for classification according to GHS criteria for this product.

Label Elements

This product does not require a hazard warning label in accordance with GHS criteria.

Hazards Not Otherwise Classified

None known if used according to instructions.

Irritation may occur when in contact with eyes and skin.

Labeling of Special Preparations (GHS): None required

According to Regulation 1994 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

3. COMPOSITION/INFORMATION ON INGREDIENTS

According to Regulation 1994 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

This product does not contain any components classified as hazardous under the referenced regulation.

CAS #	Content	Chemical Name
Trade Secret	35 - 55	Silylated Polyurethane Resin
Trade Secret	1 - 5	Plasticizer
1317-65-3	30 - 40	Calcium carbonate
Trade Secret	1 - 5	Additives
25322-69-4	10 - 20	Polypropylene glycol

4. FIRST AID MEASURES

General Advice: Upon contact, remove material from skin, eyes and clothing. If irritation persists, seek medical attention.

If Inhaled: Remove individual to fresh air if needed.

If on Skin: Wash with mild soap and water.

If in Eyes: Open eyelids and flush with running water for at least 15 minutes.

If Swallowed: Do not induce vomiting. Seek medical help immediately.

Most Important Symptoms and Effects, Both Acute and Delayed: None expected due to non-classification of the product.

Indication of Any Immediate Medical Attention and Special Treatment Needed: *Note to physician* - Symptomatic Treatment

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Use water spray, foam, dry powder when needed.

Special Hazards Arising from the Substance or Mixture

Material is a mixture of organic compounds. Compounds of carbon may arise during burning.

Advice for fire-fighters: Wear self-contained breathing apparatus and turn out gear. Use water to keep the containers cool.

Further Information

Dispose debris and contaminated clothing in accordance with regulations.

6. ACCIDENTAL RELEASE MEASURES

Further Accidental Release Measures: Slip hazard when spilled.

Personal Precautions Protective Equipment and Emergency Procedures:

Use personal protective clothing. Avoid contact with skin and eyes.

Environmental Precautions: Do not release spilled material into natural waters.

Methods and Material for Containment and Cleaning Up:

Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations. Spills should be contained, solidified, and placed in suitable containers for disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not puncture. Keep out of the reach of children.

Conditions for Safe Storage, Including any Incompatibilities

Keep from freezing. Avoid extreme temperatures.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Advice on System Design

Maintain proper ventilation.

Personal Protective Equipment:

Respiratory Protection: NIOSH respirator if needed. Use local exhaust ventilation. Do not use closed air-circulating system.

Skin Protection: Chemical resistant gloves, apron, coveralls, and boots to prevent unnecessary contact.

Eye Protection: Safety glasses, goggles, or face shield

General Safety and Hygiene Safety Measures:

Wash hands and/or face after use. Launder contaminated clothing before re-use. Always use protective equipment to avoid direct contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Low viscosity liquid

Odor: Mild

Odor Threshold: No data

Color: Off white

pH Value: Not applicable

Melting Point: Not applicable

Boiling Point: No data

Flash Point: Not applicable

Flammability: Non flammable

Lower Explosion Limit: Not applicable

Upper Explosion Limit: Not applicable

Vapor Pressure: Low

Density: 8.40 - 8.70 lbs. per gallon

Relative Density: 1.01 - 1.04 grams / cm³

Vapor Density: Low

Partition Coefficient n-octanol/water (log Pow): No data

Self-Ignition Temperature: Not Applicable

Solubility in Water: Insoluble

Miscibility in Water: Not miscible

Evaporation Rate: Low

Other Information: Moisture cure product. Product will start curing in the presence of moisture.

10. STABILITY AND REACTIVITY

Reactivity: Stable

Chemical Stability: Stable

Possibility of Hazardous Reactions: None, product is stable

Conditions to avoid: Extreme temperatures

Incompatible Materials: Water. Product is a moisture curing material.

Hazardous Decomposition Products: None known

11. TOXICOLOGICAL INFORMATION

No Data Available

Primary routes of exposure: Respiratory, eyes, skin. Ingestion is not likely but might cause gastric disturbances.

Acute Toxicity/Effects

Acute toxicity: May cause irritation upon contact.

Chronic Toxicity Effects

Repeated Dose Toxicity: No data available

Genetic Toxicity: No data available

Carcinogenicity: Not carcinogenic

Reproductive Toxicity: No data available

Teratogenicity: No data available

Experiences in Humans: No data available

Other Information:

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Abide by all state, federal and local regulations

14. TRANSPORTATION INFORMATION

Proper Shipping Name: Not applicable

Proper Hazard Class: Not hazardous

Hazard Code: None hazardous

Bill of Lading Description: Adhesives, NOI

15. REGULATORY INFORMATION

Federal Regulations:

Registration Status:

TSCA: Chemicals contained in the product are either listed or exempt in the U.S. EPA TSCA inventory list.

SARA Title III, Section 312 Hazard Class: None

EPA SARA Title III Section 312: None

NFPA Hazard Codes:

Health: 1 Fire: 0

Reactivity: 0 Special:

HMIS rating:

Health: 1 Flammability: 0

Physical Hazard: 0

16. OTHER INFORMATION

SDS prepared for: Milliken Floors

SDS prepared on: April 6, 2017

Milliken Floors believes the data set forth herein is accurate as of the date hereof. Milliken makes no warranty with respect hereto and expressly disclaims all liability of reliance thereon. All data is offered solely for consideration, investigation, and verification.