

# GLUEDOWN LVT - ALL ABOUT WOOD

French Oak, Vintage Oak



<b>Construction</b>	High Performance Luxury Vinyl Tile
<b>Finish</b>	ProGuard MAX™ UV-Cured Urethane
<b>Wear Layer Thickness</b>	0.55 mm
<b>Overall Thickness</b>	2.5 mm
<b>Edge Profile</b>	Micro Bevel with Matte Bevel Technology™
<b>Product Weight</b>	4000 g/m <sup>2</sup>

## PERFORMANCE

<b>Flammability/Smoke Emissions (EN 13501-1)</b>	Class Bfl-s1
<b>Use Classification (EN ISO 10874)</b>	Class 33 Heavy Commercial, Class 42 General Light Industrial
<b>Dimensional Stability (EN ISO 23999)</b>	Requirement - ≤0.25 %, Curl ≤2 mm. Typical results - ≤0.10 %, Curl ≤0.5 mm
<b>Residual Indentation (EN ISO 24343-1)</b>	≤0.1 mm
<b>Colour Fastness to Light (EN ISO 105-B02)</b>	≥6
<b>Castor Chair Resistance (Type W) (EN ISO 4918)</b>	Pass
<b>Chemical Resistance (EN ISO 26987)</b>	Excellent
<b>Electrostatic Propensity (EN ISO 1815)</b>	≤2.0 kV
<b>Slip Resistance (EN16165 Annex B / DIN 51130 - Ramp)</b>	R10
<b>Slip Resistance (EN16165 Annex C / BS 7976 - Pendulum)</b>	≥61 dry; ≥39 wet (low slip potential ≥36)

## INSTALLATION

Full spread of permanent adhesive

## TILE/PLANK SIZE

200 x 1000mm

## ENVIRONMENTAL

Minimum of 20% recycled content by total product weight (Pre Consumer internal waste)

Manufactured in ISO14001 certified location

M/PACT Carbon Neutral Floors,  
10.39 kg CO<sub>2</sub> e/m<sup>2</sup> Embodied Carbon (EPD calculation A1-A4)  
Cradle to Gate footprint 100% off set

Orthophthalate and REACH SVHC free- compliant to WELL feature requirement for Enhanced Material Restrictions

Single polymer construction for ease of end-of-life recycling

## BOX QUANTITY

20 pieces / 4.0m<sup>2</sup>

## WARRANTIES

15 year wear warranty

## CERTIFICATIONS


## INSTALLATION

Ashlar Random	Herringbone

## CE

DOP 1004-06 BS EN 651						