

# Milliken® Cable Management Vis™ Tape



## VT-565 and VT-565DET

*565 kg pull tape in standard,  
detectable options*

Pull tape, made of low friction, high tenacity, abrasion resistant yarns and printed using MPrint™ technology.

### Specifications

|                         |                             |
|-------------------------|-----------------------------|
| <b>Tensile Strength</b> | 565 kg (Minimum)            |
| <b>Working Load</b>     | 565 kg                      |
| <b>Approx. Width</b>    | 12.5 mm +/- 10%             |
| <b>Approx. Weight</b>   | 9.5 kg (13.5 kg DET) per km |
| <b>Color</b>            | White                       |
| <b>Print Color</b>      | Black                       |

| STANDARD REEL LENGTHS | VT-565 | VT-565DET |
|-----------------------|--------|-----------|
| 300 m                 | ●      |           |
| 900 m                 | ●      | ●         |
| 1,500 m               | ●      | ●         |
| 30,000 m              | ●      |           |

### Features & Benefits

- Pre-lubricated
- Printed with sequential meter markings
- Packaging: UV resistant white plastic wrap
- Detectable wire is a 22 ga solid tinned copper conductor, 14 ohms per km resistance
- Palletised and shrink wrapped: All rolls 900 m and smaller have 36 spools per pallet; rolls 900 m have 27 spools per pallet