

# Mosaic 95

Milliken

## ADHESIVE

### For Mixed Media

Carpet Tile, 5 mm FlexForm™ LVT,  
5 mm FlexForm™ Sound LVT, 4.5 mm RigidForm Free™



UP TO 11



UP TO 95%



DRY TIME  
30+ min



WORKING TIME  
8 hrs



ROLL FLOOR  
within 1 hr (LVT Only)



CURE TIME  
6 hrs



LIGHT TRAFFIC  
12 hrs



HEAVY TRAFFIC  
24 hrs



HEAVY ROLLING  
LOADS : 72 hrs



4-Gallon Pail  
Trowel

## Aggressive-Tack Mixed-Media Adhesive

For use with RH up to **95%**

Installation after new pour: **45 days**



The Benefits of  
Milliken Adhesives

Milliken offers adhesive solutions for any scenario:

- Modular carpet, LVT, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required

  
1/16" x 1/16" x 1/32"  
U-Notch

### FLOORING TYPE

Carpet Tile  
5 mm FlexForm LVT  
5mm FlexForm  
Sound LVT<sup>1</sup>  
4.5 mm RigidForm Free™<sup>2</sup>

<sup>1</sup> Semi-Wet or Wet application  
required

<sup>2</sup> Wet application required

ESTIMATED COVERAGE  
185-245 sf/gal



3/8"  
Short Nap  
Paint Roller

### FLOORING TYPE

Carpet Tile

ESTIMATED COVERAGE  
200 - 260 sf/gal

SCAN THE QR CODE BELOW  
FOR MORE INFORMATION



# Mosaic 95



<b>PRODUCT CHARACTERISTICS</b>	Product Classification	Trowel pressure sensitive adhesive
	Base Chemistry	Acrylic polymer
	Solids Content	40% to 60%
	Density	8.3 lbs. per U.S. gal. (1.0 g per mL)
	Appearance	Light tan
	Application	Trowel (Carpet Tile & LVT) or roller (carpet tile only)
	Flash Point	> 212°F (100°C)
	Shelf Life	2 years (unopened)
<b>MOISTURE</b>	RH	95%
	pH	Up to 11
<b>TIME</b>	Flash Time (permanent bond - LVT only)	0 min
	Flash Time (pressure-sensitive - carpet tile)	30 min or until dry
	Working Time	15 mins (permanent bond- LVT only), 8 hrs (PSA)
	Roll & Cross Roll Floor (75- 100lb roller)	Within 1 hour after installation (LVT only)
<b>TRAFFIC</b>	Light Traffic	12 hrs
	Heavy Traffic	24 hrs
	Heavy Rolling Loads	72 hrs
<b>SUSTAINABILITY</b>	Total VOCs	0.5 mg/m <sup>3</sup> or less
	Compliant with	California DPH Section 01350 Version 1.2
	Certifications	CRI Green Label Plus

**STORAGE** This product should be stored at temperatures between 50-90°F (10-32° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing.

**CAUTION** DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

**WARRANTY** For Milliken installation instructions and warranties, visit [millikenfloors.com](https://millikenfloors.com).

