

# Mosaic 95

Milliken

## ADHESIVE

Carpet Tile, 5 mm FlexFORM™ LVT  
5 mm FlexFORM™ Sound LVT, 4.5 mm RigidFORM Free™ LVT,  
HybridFORM™



UP TO 11



UP TO 95%



DRY TIME  
30+ min



WORKING TIME  
8 hrs



ROLL FLOOR  
within 1 hr (Resilient Only)



CURE TIME  
6 hrs



LIGHT TRAFFIC  
12 hrs



HEAVY TRAFFIC  
14 hrs



HEAVY ROLLING  
LOADS: 72 hrs



4-Gallon Pail  
Trowel

## Aggressive-Tack Mixed-Media Adhesive

For use with RH up to **95%**


Installation after new pour: **45 days**



The Benefits of  
Milliken Adhesives

Milliken offers adhesive solutions for any scenario:

- Modular carpet, resilient flooring, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required



1/16" x 1/16" x 1/32"  
U-Notch

### FLOORING TYPE

Carpet Tile  
HybridFORM  
<sup>1</sup> Dry set only  
5 mm FlexForm LVT  
5mm FlexForm Sound LVT<sup>1</sup>  
<sup>2</sup> Semi-Wet  
4.5 mm RigidForm Free™<sup>2</sup>  
<sup>3</sup> Wet application required  
ESTIMATED COVERAGE  
185-245 sf/gal



3/8"  
Short Nap  
Paint Roller

### FLOORING TYPE

Carpet Tile  
<sup>1</sup> Dry set only  
ESTIMATED COVERAGE  
200-260 sf/gal

SCAN THE QR CODE BELOW  
FOR MORE INFORMATION



# Mosaic 95

|                                |   |   |
|--------------------------------|---|---|
| <b>PRODUCT CHARACTERISTICS</b> | Product Classification                        | Trowel pressure sensitive adhesive                            |
|                                | Base Chemistry                                | Acrylic polymer   |
|                                | Solids Content                                | 40% to 60%  |
|                                | Density                                       | 8.3 lbs. per U.S. gal. (1.0 g per mL)                         |
|                                | Appearance                                    | Light tan   |
|                                | Application                                   | Trowel (carpet tile & resilient) or roller (carpet tile only) |
|                                | Flash Point                                   | > 212°F (100°C)   |
|                                | Shelf Life                                    | 2 years (unopened)  |
| <b>MOISTURE</b>                | RH  | 95%   |
|                                | pH  | Up to 11  |
| <b>TIME</b>                    | Flash Time (permanent bond - LVT only)        | 0 min   |
|                                | Flash Time (pressure-sensitive - carpet tile) | 30 min or until dry   |
|                                | Working Time                                  | 15 mins (permanent bond- LVT only), 8 hrs (PSA)               |
|                                | Roll & Cross Roll Floor (75- 100lb roller)    | Within 1 hour after installation (LVT only)                   |
| <b>TRAFFIC</b>                 | Light Traffic                                 | 12 hrs  |
|                                | Heavy Traffic                                 | 24 hrs  |
|                                | Heavy Rolling Loads                           | 72 hrs  |
| <b>SUSTAINABILITY</b>          | Total VOCs                                    | 0.5 mg/m <sup>3</sup> or less                                 |
|                                | Compliant with                                | California DPH Section 01350 Version 1.2                      |
|                                | Certifications                                | CRI Green Label Plus  |

**STORAGE** This product should be stored at temperatures between 50-90°F (10-32° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing.

**CAUTION** DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately.  
KEEP OUT OF REACH OF CHILDREN.

**WARRANTY** For Milliken installation instructions and warranties, visit [millikenfloors.com](http://millikenfloors.com).

Customer Concierge 800.824.2246 | [millikenfloors.com](http://millikenfloors.com)  
©2023 Milliken & Company | Design ©Milliken & Company | Made in the USA