

IN SITU

Area / Move



Construction	Tufted, Level Loop Pile
Face Fibre	Nylon 6
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	420 g/m ²
Gauge	40 / 10 cm
Rows	56 / 10 cm
Tuft Density	220,472 /m ²
Finished Pile Height	3.0 mm
Standard Backing	Comfort Lite 90% Recycled content Polyurethane Available with TractionBack® on request
Nominal Total Thickness	8.9 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	3700 g/m ²
Tiles per Box	22 (5.5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2018)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	30 dB
Sound Absorption (ISO354)	0.3 Class D
Alpha s values	125Hz 0.00, 250Hz 0.05, 500Hz 0.35, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.40

ENVIRONMENTAL

60% recycled content by total product weight
 Manufactured in ISO14001 certified location using renewable sources
 M/PACT Carbon Neutral Floors,
 6.86 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A3)
 Cradle to Gate footprint 100% off set


WARRANTIES

12 year wear warranty
 Lifetime Antistatic guarantee
 Latent Defects guarantee

CERTIFICATIONS

www.millikenfloors.com/gb/tech

INSTALLATION



CE / UKCA

DOP-2895-1004-02 BS EN 14041:2018	DOP-0338-1004-02 BS EN 14041:2018			