

Declare.

Flexform Sound Milliken

Final Assembly: Cheong-ju Plant, Korea

Life Expectancy: 25 Year(s)

End of Life Options: Recyclable (100%)

Ingredients:

Calcium Carbonate; Polyvinyl chloride; Dioctyl terphthalate, DOTP; 1,2,3-Propanetriol; 2-hydroxy-2-methyl-phenyl-propan-1-one; 2-Propenoic acid, monoester with 1,2-propanediol; Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester; Carbon black; Di(2-ethylhexyl)adipate; Dipropylene Glycol Diacrylate; Distillates (petroleum), hydrotreated light paraffinic; Fatty acids, saturated, linear, with even-numbered C-chain, number of C-atoms ≥ 14 , with terminating carboxyl group; Hexamethylene Diacrylate; Hexanedioic acid, polymer with 1,2-ethanediol and 1,6-diisocyanato-2,2,4(or 2,4,4)-trimethylhexane, 2-hydroxyethyl acrylate-blocked; Methanone, (1-hydroxycyclohexyl)phenyl-; Silica, amorphous, fumed, cryst.-free; Trimethylolpropane Triacrylate

Living Building Challenge Criteria:

I-13 Red List:

- | | |
|--|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input checked="" type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

MKN-0032

EXP. 01 APR 2024

Original Issue Date: 2020