

## **OBEX™ Grid Cut - 16mm Closed M50 ENTRANCE FLOORING**

<b>130</b>	Entrance Flooring Tiles
<b>Location:</b>	Refer to Finishes Schedule
<b>Preparation:</b>	According to the guidelines laid out in the Contract Flooring Association's "Guide to Contract Flooring".
<b>Tiles:</b>	Manufacturer and reference Milliken "OBEX™ Grid Cut - 16mm Closed"
<b>Size:</b>	Grid: 210 x 210mm nominal
<b>Colour:</b>	Refer to Finishes schedule
<b>Pattern:</b>	Refer to Finishes schedule
<b>Construction:</b>	Cut Pile
<b>Fibre:</b>	ECONYL® 100% regenerated polyamide, multi/monofilaments dual fibres
<b>Backing:</b>	100% UV-Resistant PVC
<b>Yarn:</b>	Twisted and heat-set
<b>Pattern:</b>	Galaxy
<b>Finished Dimensions:</b>	<b>Grid</b> = 198 x 198mm <b>Grid Thickness</b> = 16.0 mm <b>Total Thickness</b> = 18.0 mm <b>Total Weight</b> = 11,130 g/m <sup>2</sup>
<b>Warranties:</b>	1-Year Manufacturing Defect Warranty 5-Year Wear Warranty
<b>Method of Laying:</b>	By Milliken Approved Contractor. In strict accordance with Milliken installation recommendations.
<b>Special Requirements:</b>	Maintenance method must be demonstrated to ensure not only appearance retention but also to leave OBEX in hygienic condition.