

Milliken® Daran® 2026

TECHNICAL DATA

Description

Daran® 2026 is an aqueous anionic copolymer emulsion designed as a high barrier adhesive and extrusion coating primer.

Applications

- High barrier/high bond extrusion primer for nylon
- High barrier adhesive for BOPP/BOPP film
- Dry bond laminations
- Extrusion coating primer

Storage

Protect from the effects of weathering and light. Store at temperatures between 5 and 30 °C. Once opened, containers should be resealed immediately after each removal of the product. Contact with common metals such as mild steel copper, zinc, or aluminum should be avoided.

Features

- Oxygen and moisture vapor barrier performance
- Bonds plastic films to paper, films to films
- Adhere to paper substrates and plastic films without need for an additional primer

General Characteristics

Appearance	Creamy white
Non-Volatile Content	45%
pH	1.5
Density	1.25 g/cm ³ , 25°C
Viscosity*	12 mPa sec
Surface Tension	38 dynes/cm
Alcohol Tolerant	No
Recommended Shelf Life	6 months (unopened containers at 25 °C)

*Brookfield LVF, Spindle #1, 50 rpm

Safety and Handling

Please refer to our safety data sheet for information relating to product safety.

Please contact your Milliken representative for further product information including chemical registrations, food contact status, and other regulatory details.

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.

NORTH AMERICA Spartanburg, SC, USA Tel: 800-910-5592 Fax: 864-503-2430 millichem@milliken.com	EUROPE Gent, Belgium Tel: 32-9-265-1100 Fax: 32-9-265-1195 eurochem@milliken.com	LATIN AMERICA Sao Paulo, Brazil Tel: 55-11-3043-7942 Fax: 55-11-3043-7096 lachem@milliken.com	LATIN AMERICA Mexico City, Mexico Tel: 52-55-3088 3600 Fax: 52-55-9000 2643 lachem@milliken.com	ASIA Singapore Tel: 65-6377-0770 Fax: 65-6377-0990 asiachem@milliken.com	ASIA Shanghai Tel: 86-21 6145-5555 Fax: 86-21 6145-5558 asiachem@milliken.com	ASIA Pune, India Tel: 91.20.6730.7501 Fax: 91.20.6730.7514 asiachem@milliken.com
--	--	---	---	--	---	--