

# Declare.



## Local Measure, Lumenology - Americas (Flexform Standard US 4-8mm) Milliken & Company

**Final Assembly:** Fostoria, Ohio, USA

**Life Expectancy:** 25 Year(s)

**End of Life Options:** Recyclable (100%)

### Ingredients:

Calcium carbonate; Polyvinyl chloride; Octadecaneic Acid, 10-Chloro-9-Methoxy, Methyl Ester; Dioctyl terphthalate, DOTP; Magnesium hydroxide; Glass Fiber; Soybean oil, epoxidized; Calcium Stearate; Zinc Stearate; Carbon black; Epoxy Acrylate; Hexamethylene Diacrylate; 2-hydroxyethyl Methacrylate; 2-Propenoic acid, (1-methyl-1,2-ethanediyl) bis[oxy(methyl-2,1-ethanediyl)] ester; Dipropylene Glycol Diacrylate; Propoxylated neopentyl glycol Diacrylate; Trimethylolpropane Triacrylate; 2-hydroxy-2-methyl-phenyl-propan-1-one; 2,4,6-trimethyl benzoyl diphenyl phosphine oxide

### Living Building Challenge Criteria:

#### I-13 Red List:

- |  |                             |
|--|-----------------------------|
| <input type="checkbox"/> LBC Red List Free     | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input checked="" type="checkbox"/> Declared   |                             |

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Not Applicable

MKN-0033

EXP. 01 JUN 2025

Original Issue Date: 2020