

LVT - ALL ABOUT STONE 5.0

Beton Ciré / Ceppo Grande / Terrazzo / Terrazzo Grande

Construction	High Performance Luxury Vinyl Tile FlexForm Sound™
Finish	ProGuard MAX™ UV-Cured Urethane
Wear Layer Thickness	0.55 mm
Overall Thickness	5 mm
Edge Profile	Micro Bevel with Matte Bevel Technology™
Product Weight	7600 g/m²

PERFORMANCE

Flammability/Smoke Emissions (EN 13501-1)	Class Bfl-s1
Use Classification (EN ISO 10874)	Class 33 Heavy Commercial, Class 42 General Light Industrial
Dimensional Stability (EN ISO 23999)	Requirement - $\leq 0.25\%$, Curl ≤ 2 mm. Typical results - $\leq 0.10\%$, Curl ≤ 0.5 mm
Residual Indentation (EN ISO 24343-1)	≤ 0.2 mm
Colour Fastness to Light (EN ISO 105-B02)	≥ 6
Castor Chair Resistance (Type W) (EN ISO 4918)	Pass
Chemical Resistance (EN ISO 26987)	Excellent
Electrostatic Propensity (EN ISO 1815)	≤ 2.0 kV
Impact Sound Insulation (EN ISO 717-2)	19 dB ΔL_w
Slip Resistance (EN16165 Annex B / DIN 51130 - Ramp)	R10
Slip Resistance (EN16165 Annex C / BS 7976 - Pendulum)	≥ 61 dry; ≥ 44 wet (low slip potential ≥ 36)

INSTALLATION

Full spread of tackifier adhesive

TILE/PLANK SIZE

500 x 1000mm

ENVIRONMENTAL

Minimum of $\geq 20\%$ recycled content by total product weight (Pre Consumer internal waste)

Manufactured in ISO14001 certified location

M/PACT™ Carbon Offset Floors,
19.30 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A3)
Cradle to Gate footprint 100% off set

Orthophthalate and REACH SVHC free- compliant to WELL feature requirement for Enhanced Material Restrictions

Single polymer construction for ease of end-of-life recycling

BOX QUANTITY


4 pieces / 2m²

WARRANTIES

15 year wear warranty

CERTIFICATIONS

INSTALLATION



CE

--	--	--	--	--	--	--	--