

WHALE SONG (WellBAC® Comfort)

Beluga | Humpback

Modular Tiles

When you choose M/PACT™ products, you can be sure your choice is carbon neutral. M/PACT™ carbon neutral products offset the raw materials and manufacturing carbon footprint* by using 3rd party Verified Carbon Standard Credits that support renewable energy and carbon reduction technologies to help fight climate change.

*as calculated and verified through a ISO14025/ISO14040 compliant LCA and published in third party EPD.

WELLBAC® Milliken WellBAC® open cell foam cushion provides superior durability, appearance retention and cushioning.	<p>Up to 24% greater underfoot comfort for enhanced ergonomics whilst standing.</p>	<p>Up to 50% improved acoustics for quieter, more productive spaces.</p>	<p>Industry leading moisture management with non-reactive backings to enhance the installation process.</p>	<p>3rd party Verified Red-List Free products for occupant and installer well-being.</p>	<p>Enhanced Indoor Air Quality (Low VOC) for improved occupant and installer well-being.</p>
--	---	--	---	--	--

Standard Backing	Cushion Backing WellBAC® Comfort (PVC FREE) (Non-Reactive Cushion Backing)
Acoustic Value	Noise Reduction Coefficient - NRC ≥ 0.25 Impact Sound Pressure Level - Ln,w ≤47dB
Concrete Slab Moisture Mitigation	Milliken Cushion backed tile + Non-Reactive Standard adhesive means installation 60 days after a new concrete pour, fully warranted no moisture testing required. Refer millikenfloors.com.au

Construction	Tufted, Textured Loop, Tip Shear
Tile Size	50cm x 50cm
Yarn Type	100% Solution Dyed Nylon
Stain Resist Soil Release	Built-In Protection
Dye Method	Solution Dyed
Gauge	1/12
Stitches Per Inch	11.6
Tufts	139/in ² (2,153/100cm ²)
Recyclable	100%
Nominal Total Thickness	8.7mm
Nominal Pile Thickness	2.7mm
Nominal Total Weight	94.4 oz/yd ² (3,270 g/m ²)

Flammability (Radiant Panel Test)	CHF/CRF = 3.2KW/m ² , Smoke value = 266%.min
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Static Electricity (AATCC-134) 20% R.H., 70 ° F	≤ 3.5KV
Indoor Air Quality CRI Green Label Plus™	≤0.5mg/m ³ (GLP7205)
VOC	Pass (ISO 10580:2010)
ACCS Grading	CEHD(S) 4*, REHD2 (S)6*, Suitable for Stairs
Environmental	ECS Grading - Level 4 (Certificate No. 23279) Declare - 3 rd Party Verified RED LIST FREE Cradle to Cradle - Silver Carbon Neutral Environmental Product Declaration (EPD) Health Product Declaration (HPD)

Recommended Installation Method(s)	Brick (Horizontal) Ashlar (Vertical)
Recommended Area of Use	Commercial Extra Heavy Duty
Warranties	15-year Wear Warranty
	15-year Dimensional Stability Warranty
	15-year Anti-Static Warranty
	15-year Castor Chair Wear Warranty



Alliance
Founding
Member



This WellBAC® cushion backing carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.