Milliken

Milliken® **Bind**

TECHNICAL DATA

Description

Daran[®] 8100 is an aqueous anionic copolymer emulsion for high water vapor and oxygen barrier applications where thermoformability is needed.

Applications

- Pharma base coat
- Thermoformable substrates

Storage

Protect from the effects of weathering and light. Store at temperatures between 5 and 30 °C. Once opened, containers should be resealed immediately after each removal of the product. Contact with common metals such as mild steel copper, zinc, or aluminum should be avoided.

Features

- High barrier for WVTR and OTR performance
- High crystallinity
- Thermoformable
- Good heat seal strength
- High total solids
- Low surface tension for good wettability

General Characteristics

Appearance	Creamy white		
Non-Volatile Content	60%, 110 °C, 1h (Filter Papers) 3.0 neat, pH meter		
рН			
Density	1.29 g/cm³, 25°C		
Viscosity*	22 mPa sec		
Surface Tension	32 dynes/cm		
Alcohol Tolerant	No		

*Brookfield (25 °C) LVF, Spindle #1, 60 rpm

Safety and Handling

Please refer to our safety data sheet for information relating to product safety.

Please contact your Milliken representative for further product information including chemical registrations, food contact status, and other regulatory details.

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.

NORTH AMERICA	EUROPE	LATIN AMERICA	LATIN AMERICA	ASIA	ASIA	ASIA
Spartanburg, SC, USA	Gent, Belgium	Sao Paulo, Brazil	Mexico City, Mexico	Singapore	Shanghai	Pune, India
Tel: 800-910-5592	Tel: 32-9-265-1100	Tel: 55-11-3043-7942	Tel: 52-55-3088 3600	Tel: 65-6377-0770		Tel. 91.20.6730.7501
Fax: 864-503-2430	Fax: 32-9-265-1195	Fax: 55-11-3043-7096	Fax: 52-55-9000 2643	Fax: 65-6377-0990		Fax. 91.20.6730.7514
millichem@milliken.com	eurochem@milliken.com	lachem@milliken.com	lachem@milliken.com	asiachem@milliken.com	asiachem@milliken.com	asiachem@milliken.com

@ Copyright 2024 Milliken & Company. All rights reserved. Milliken `` is a trademark of Milliken & Company. Daran* is a registered trademark of Milliken & Company. 1.4.2024

milliken.com