

## FIRST CALL - Open-Shut, On-Point LVT

### M50 RUBBER / PLASTICS / CORK / LINO / CARPET TILING

<b>130</b>	Carpet Body Tiles
<b>Location:</b>	Refer to Finishes Schedule
<b>Preparation:</b>	According to the guidelines laid out in the Contract Flooring Association's "Guide to Contract Flooring".
<b>LVT Tiles:</b>	Manufacturer and reference Milliken "First Call - Open-Shut, On-Point LVT"
<b>Size:</b>	250 x 1500mm nominal to be die cut for consistent tolerance.
<b>Colour:</b>	Refer to Finishes schedule
<b>Pattern:</b>	Refer to Finishes schedule
<b>Construction:</b>	High Performance Luxury Vinyl Tile. FlexForm Sound™
<b>Finish:</b>	ProGuard MAX™ UV-Cured Urethane
<b>Backing:</b>	FlexForm Sound™
<b>Pattern:</b>	First Call - Open-Shut, On-Point
<b>Finished Dimensions:</b>	<b>Module</b> = 250 x 1500mm <b>Total Thickness</b> = 5mm <b>Product Weight</b> = 8 kg/m <sup>2</sup>
<b>Warranties:</b>	15 year wear warranty
<b>Method of Laying:</b>	By Milliken Approved Contractor. In strict accordance with Milliken installation recommendations.
<b>Special Requirements:</b>	Maintenance method must be demonstrated to ensure not only appearance retention but also to leave carpet in hygienic condition.