

$Milliken^{*}$

10% Potassium Acetate

TECHNICAL DATA

Description

10% Potassium Acetate is an accelerator additive for unsaturated polyesters and pot life stabilizer for two-component PU systems.

Applications

o Unsaturated polyesters in solvent-containing systems

Storage

Protect from the effects of weathering and store at temperatures between 5 and 30 °C. Once opened, containers should be resealed immediately after each removal of the product. With prolonged storage of opened containers it is advisable to scavenge the vapor space above the product with nitrogen before resealing the containers.

Features

- Potassium acetate dissolved in diethylene glycol which combined with cobalt supports the accelerating effect in unsaturated polyesters dissolved in styrene
- Decreases discoloration of UPS-Systems caused by cobalt
- Capable of stabilizing the rheological and the pot life behavior of water-based two-component PU systems
- Completely miscible with water, alcohols and other polar solvents

General Characteristics

Metal Content	K: 9.80 - 10.20 %
Weight per Gallon	9.83 - 10.33 lb/gal 25°C, D1963

Safety and Handling

Please refer to our safety data sheet for information relating to product safety.

Please contact your Milliken representative for further product information including chemical registrations, food contact status, and other regulatory details.

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.

NORTH AMERICA Spartanburg, SC, USA Tel: 800-910-5592 Fax: 864-503-2430 EUROPE Gent, Belgium Tel: 32-9-265-1100 Fax: 32-9-265-1195 eurochem@milliken.co

LATIN AMERICA Sao Paulo, Brazil Tel: 55-11-3043-7942 Fax: 55-11-3043-7096 LATIN AMERICA
Mexico City, Mexico
Tel: 52-55-3088 3600
Fax: 52-55-9000 2643

ASIA Singapore Tel: 65-6377-0770 Fax: 65-6377-0990

ASIA Shanghai Tel: 86-21 6145-5555 Fax: 86-21 6145-5558 ASIA Pune, India Tel. 91.20.6730.7501 Fax. 91.20.6730.7514 asiachem@milliken.com