

Fortify Foundations 2.5 Milliken

Final Assembly: Zhenjiang, Jiangsu, China

Life Expectancy: 25 Year(s)

End of Life Options: Recyclable (100%)

Ingredients:

Calcium carbonate; Polyvinyl chloride; Octadecaneoic Acid, 10-Chloro-9-Methoxy, Methyl Ester; Dioctyl terphthalate, DOTP; Epoxidized Soybean Oil; Calcium Stearate; Zinc Stearate; Carbon black; Epoxy Acrylate; Hexamethylene Diacrylate; 2-Propenoic acid, (1-methyl-1,2-ethanediyl) bis[oxy(methyl-2,1-ethanediyl)] ester; Dipropylene Glycol Diacrylate; Trimethylolpropane Triacrylate; 2-hydroxyethyl Methacrylate; Propoxylated neopentyl glycol Diacrylate; 2,4,6-trimethyl benzoyl diphenyl phosphine oxide; 2-hydroxy-2-methyl-phenyl-propan-1-one

Living Building Challenge Criteria:

I-13 Red List:

☐ LBC Red List Free % Disclosed: 100% at 100ppm

☐ LBC Red List Approved VOC Content: Not Applicable

■ Declared

I-10 Interior Performance: CDPH Standard Method v1.1-2010

I-14 Responsible Sourcing: Not Applicable

MKN-0010 EXP. 01 APR 2024 Original Issue Date: 2015