

Declare. SM

FlexForm Sound™ LVT (Loose Lay) Milliken

Final Assembly: Jiangsu Province, P.R. China

Life Expectancy: 25 Year(s)

End of Life Options: Recyclable (100%)

Ingredients:

Calcium carbonate; Polyvinyl chloride; Glass Fiber; Dioctyl terphthalate, DOTP; Aluminum hydroxide; Iron; 2-Propenoic acid, polymer with butyl 2-propenoate and ethenylbenzene; Polyethylene; 2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]undecane, 3,9-bis(octadecyloxy)-; Calcium Stearate; Zinc Stearate; epoxy acrylic resin; Carbon black; 2-Propenoic acid, (1-methyl-1,2-ethanediy) bis[oxy(methyl-2,1-ethanediy)] ester; Trimethylolpropane Triacrylate.; Benzophenone

Living Building Challenge Criteria:

I-13 Red List:

- | | |
|--|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input checked="" type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

MKN-0035

EXP. 01 JUN 2023

Original Issue Date: 2020