

## FORMWORK 3.0

### M50 CARPET TILING

130

Carpet Body Tiles

**Location:**

Refer to Finishes Schedule

**Preparation:**

According to the guidelines laid out in the Contract Flooring Association's "Guide to Contract Flooring".

**Carpet Tiles:**

Manufacturer and reference Milliken "FORMWORK 3.0" tiles

**Size:**

FORMWORK 3.0 tiles: 5000 x 5000mm to be die cut for consistent tolerance

**Colour:**

Refer to Finishes schedule

**Pattern:**

Refer to Finishes schedule

**Construction:**

Tufted Level Loop Pile

**Fibre:**

Solution Dyed Nylon 20% recycled content  
Chosen for soil hiding and resilience.

**Backing:**

High-density, open-cell polyurethane foam. 90% recycled  
Improved comfort, acoustics and wear performance.

**Yarn:**

Spun yarn, heat set.

**Pattern:**

Formwork 3.0

**Finished Dimensions:**

**Module** = 5000 x 5000mm

**Pile Weight** = 269 g/m<sup>2</sup>,

**Pile Height** = 2.2mm

**Tuft Density** = 208,661 per m<sup>2</sup>

**Total Thickness** = 8.6 mm

**Total Weight** = 3800 g/m<sup>2</sup>

**Warranties:**

12 year wear warranty

Lifetime Antistatic

Latent Defects

**Method of Laying:**

By Milliken Approved Contractor.

In strict accordance with Milliken installation recommendations.

**Special Requirements:**

Maintenance method must be demonstrated to ensure not only appearance retention but also to leave carpet in hygienic condition.